CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHED:

Corner not previously established.

T5S R40 EH-21



DESCRIPTION OF CORNER EVIDENCE FOUND:

None found.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED TO MONUMENT THE ORIGINAL LOCATION OF THIS CORNER:

At position by Survey I set a 5/8" x 30" iron pin, 28" in the ground, with 2 1/2" aluminum cap marked as shown below, from which:

NEW BEARING OBJECTS:

A 9" Douglas Fir bears South 70° East, a dist. of 32.60 ft, marked S 1/16 S12 BT A 5" Douglas Fir bears South 26° West, a dist. of 8.20 ft, marked S 1/16 S11 BT

Set steel fence post approx. 1 ft. Southeast

I hereby certify that the corner was monumented on October 21, 2021. Witnesses: Kyle Tucker, Emmitt Ambert

REGISTERED **PROFESSIONAL** LAND. OREGON June 2, 2010 JEFFREY S. HSU 83571

Renewal Date: June 30, 2023

GRIFFITH & BAGAZZ T5S R40E S 1/16 **S12 S11 OPLS 83571** 2021

UNION COUNTY SURVEYOR DEPUTY 044-2021R

I used a steel tape and magnetic compass in the establishment of the new accessories. I use 14° East declination. Distances are to a 60d spike driven into the right side of the root crown of th bearing trees. Bearings are to a brass washer marked OPLS 83571 in the BT blaze of the new bearing trees.