CERTIFIED RECORD OF LAND CORNER MONUMENTATION

Original survey by W.B. Barr, under Contract 433, dated April 1882.

Planted a limestone 20x12x4 ins., 14 ins. in ground for Corner to Sec. 23, 24, 25, 26 marked with two notches on the South and one notch on the east sides, from which:

A pine 5 in. dia. bears N84°E 110 lks. dist., marked T5S R40E S24 BT.

A pine 4 in. dia. bears S74°E 150 lks. dist., marked T5S R40E S25 BT.

A pine 10 in. dia. bears N25°W 150 lks. dist., marked T5S R40E S23 BT.

A pine 6 in. dia. bears S41°W 88 lks. dist., marked T5S R40E S26 BT.

<i>DIAGRAM</i> T5S R40E	
23 24 26 25	

Description of corner evidence found:

Found the rotted remains of the original N.W. bearing tree a 20" diameter Ponderosa Pine stump with scribing "BT" visible on an exposed single blaze. We find fragments of decayed wood in the vicinity of the original N.E. bearing tree with illegible scribing visible, the original location cannot be determined.

No additional evidence of the original corner stone or of the remaining bearing trees was found.



T5S R40E S23 S24

S26 S25 PLS 1099

1984

Description of monument and accessories I established to perpetuate the original location of this corner:

At the original corner position determined at record bearing and distance from the only remaining original bearing tree, we set a 2"x30" aluminum pipe, 20" in the ground in an NE-SW fence line, with aluminum cap, marked:

The original NW hearing tree a 20" porders a 20" UNION CO. SURVEYOR

The original NW bearing tree a 20" Ponderosa Pine stump, previously described, bears N25°W 99.0 feet. And new bearing trees:

A 12" Douglas Fir scribed "T5S R40E S24 BT" on a double blaze bears N80°E 39.1 feet.

A 16" Ponderosa Pine, scribed "T5S R40E S25 BT" on a double blaze bears S73°E 22.8 feet.

A 10" Ponderosa Pine, scribed "T5S R40E S26 BT" on a double blaze, bears S43°W 90.0 feet.

And a 10" Ponderosa Pine, scribed "T5S R40E S23 BT" on a double blaze bears N75°W 43.5 feet.

Attached brass washer, marked "LS 1099" to lower blaze of new bearing trees. Placed steel fence post with "Attention" sign attached, approx. 6 ft. north of corner. Staff compass (20° East Declination) steel tape.

August 6, 1984

Witnesses:

Gary Langlitz, Deputy County Surveyor Dave Dahlstrom, U.S. Forest Service Greg Quibell

Office of		
-	County of	
State of here	the partition the same and the	
for record on the	by certify that the within instrument was fil	ed in this office
to record on the day of		T

(COUNTY OFFICIAL) by(DEPUTY)

UNION COUNTY
SURVEYOR

8-24-84 Date Received 0-798-276

Date Filed **8-24-84**

BY G. LANGLITZ DEPUTY

File No. 933-84 R

Form R6-7100-57 (9/71)