


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

A-13.5

History of original corner establishment:

SURVEYED BY: P. GRIFFIN, 1993, GROUP NO. 1000 AND 1484

13.425 From this point, the original closing cor. of sec. 3 and 4, T6S R41 E, bears North, 0.460 chs dist., monumented with the original basalt stone, 17 x 14 x 4 ins., loosely set at the center of a stone mound with no marks, from which the remains of the original bearing trees:



A root hole, bears N.57°E., 70 lks. dist. with pine log, 30 ins. diam., alongside, with scribe mark S on upper blaze and BT on lower blaze.

A ponderosa pine, 33 ins. diam., bears S.85°E., 74 lks. dist. with scribe marks 41 E S3 on upper blaze and BT on lower, partially healed blaze. (Record, S.82°E.)

A root hole, bears S.29°W., 90 lks. dist. with pine log alongside, 25 ins. diam., with scribe marks T6S visible on upper blaze and BT on lower blaze.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, in a mound of stone, 3 ft. base, to top, with brass cap, from which:

A lodgepole pine, 9 ins. diam., bears S.51°E., 11 lks. dist. mkd. T6S R41E S3 CC BT.

A ponderosa pine, 13 ins. diam., bears S.16¼°W., 56 lks. dist. mkd. T6S R41E S4 CC BT.

Deposit a white "DEEP-1" magnetic marker at the base the corner stone alongside, and set a 6 ft. steel fence post alongside the stainless steel post.

Description of corner evidence found:

Found a 3" BLM brass cap, in mound of stone to cap with T post 1'± NW of cor., from which:

A lodgepole pine, 8" diam., bears S.51°10'E., 6.91', with a 19" x 3" blaze, (not legible).

A ponderosa pine, 9" diam., bears S.15°00'W., 37.53', with a 25" x 3" blaze, (not legible).

A ponderosa pine, 32" diam., bears S.85°00'E., 48.73', with a 2' blaze (not legible).

Description of monument and accessories I established to perpetuate the original location of this corner:

A ponderosa pine, 12" diam., bears N.50°18'E., 28.34', with 6" x 3" blaze, scribed "X BT".

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

UNION COUNTY SURVEYOR

Date Received 1-4-2006

Date Filed 9/19/2006

By R. ROBINSON, Deputy

File No. 002-2006R

REGISTERED PROFESSIONAL LAND SURVEYOR

M. J. Stoll 10/04

OREGON JULY 19, 1983
RONALD E. STOLL
2058

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 20____
_____ by _____
(COUNTY OFFICIAL) (DEPUTY)