
LATIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner not previously established.

T5S R41 E O/P-16



DESCRIPTION OF CORNER EVIDENCE FOUND:

None

See Survey Number 035-2012

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a 5/8" x 30" iron rod with 2 ½" Aluminum Cap marked as shown, 25 ins. in the ground, in a collar of stone 1 ½ ft. diam., from which:

BEARING TREES:

- A 5 in. Ponderosa Pine bears North 82° East, a distance of 21.00 feet, marked X BT.
- a 5 in. Ponderosa Pine bears South $48\,^{\circ}$ West, a distance of 8.05 feet, marked X BT.
- I hereby certify that the corner was set on October 23, 2012.
- I set a steel fencepost 1 foot South of the corner monument.

REGISTERED
PROFESSIONAL
LAND SURVEYOR

OREGON
June 2, 2010

JEFFERY S. HSU
83571

Renewal Date: June 30, 2013

GRIFFITH & SLACE TO SELECT TO SELECT

SURVEYOR

Date Received 11/5/12

Date Filed 11/5/12

UNION COUNTY

File Number 069 - 2012 12

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 16° East declination, the distances are to a 60d spike driven into the root crown at the right side of the bearing trees. Attached brass washer marked OPLS 83571 to BT blaze.