

445

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
19.245	<p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 22 S 23 1991</p> <p>from which</p> <p style="padding-left: 40px;">A larch, 35 ins. diam., bears S. 45° E., 26 lks. dist., mkd. S 1/16 S23 BT.</p> <p style="padding-left: 40px;">A larch, 8 ins. diam., bears N. 30° W., 26 lks. dist., mkd. S 1/16 S22 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend SW. slope.</p>
38.490	<p>The ¼ sec. cor. of secs. 22 and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 22 ¼ S 23 1971</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears S. 68° E., 29 lks. dist., with fragmentary scribe marks and axe marks in opened blaze. (Record, S. 71° E.)</p> <p style="padding-left: 40px;">A root hole, bears S. 70° W., 31 lks. dist., with rotten pine log alongside, 30 ins. diam., with axe marks.</p> <p>and bearing trees mkd. by Albright</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 60½° E., 44 lks. dist., with healed blaze. (Record, N. 62° E.)</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 18½° W., 63 lks. dist., with healed blaze. (Record, S. 20° W.)</p>
	<p>N. 1° 21' 00" E., beginning new measurement.</p> <p>Descend NW slope.</p>
10.140	<p>Point for the S-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

M. E. Allen

File No.

C88-2013R

446

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	<p style="text-align: center;">S-N 1/64 S 22 S 23 1991</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 89° E., 61 lks. dist., mkd. SN 1/64 S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 27 ins. diam., bears S. 19° W., 139 lks. dist., mkd. SN 1/64 S22 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
10.30	Left bank of Catherine Creek, course SW.
11.30	Right bank of Catherine Creek.
12.15	Graveled road, 25 lks. wide, bears N. 70° E. and S. 55° W.; asc. SE. slope.
20.280	Point for the N 1/16 sec. cor. of secs. 22 and 23.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	N 1/16 S 22 S 23 1991
	from which
	A Douglas fir, 20 ins. diam., bears N. 41° E., 45 lks. dist., mkd. N 1/16 S23 BT.
	A ponderosa pine, 16 ins. diam., bears N. 35° W., 40 lks. dist., mkd. N 1/16 S22 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	The corner is located on a steep SE. slope, 75 lks. W. of a ravine, drains S. 30° E.
	Continue to ascend SE. slope, through moderate timber and light undergrowth.
30.00	Leave timber.
40.560	The cor. of secs. 14, 15, 22, and 23, monumented with the original slate stone, 14 x 12 x 3 ins. (record, 16 x 14 x 4 ins.), firmly set, projecting 6 ins. above ground, with 3 small notches on the S. edge and 2 grooves on the E. face.

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>RL Gillman</i>
Case No.	088-2013R