

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

| CHAINS | | | | | | | | | | | | | | | | | |
|---|---|--|---------------|--------|------------|--------|----|--------------|-----------|--|---|--|------|--------|------|--|------|
| | <p>From this point, triangulation station "BOTTLE," established by the United States Army Corps of Engineers in 1973, bears S. 85° 35' 50" E., 7.243 chs. dist., monumented with a brass tablet, 4 ins. diam., firmly set in bedrock, with top mkd. CORPS OF ENGINEERS TRIANGULATION STATION BOTTLE 1973 WALLA WALLA DISTRICT DEPT OF THE ARMY and a triangle in the center.</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>S. 89° 15' 00" W., bet. secs. 23 and 26.</p> <p>Descend W. slope through logging slash.</p> | | | | | | | | | | | | | | | | |
| 15.665 | <p>Remains of an original line tree, a sawed pine stump, 66 ins. diam., no marks.</p> <p>At the center of the stump drive a railroad spike flush with the stump, mkd. X on the top, from which</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 54° 22' E., 15.15 lks. dist., with top mkd. RM AP S23 10 FT TO COR 1991 and an arrow pointing to the corner.</p> <p>A stainless steel post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears S. 46° 57' 30" E., 15.15 lks. dist., with brass cap mkd. RM AP S26 10 FT TO COR 1991 and an arrow pointing to the corner. Set a white "DEEP-1" magnetic marker at the base of this reference monument.</p> | | | | | | | | | | | | | | | | |
| | <p>S. 89° 46' 30" W., beginning new measurement.</p> <p>Descend W. slope through medium timber and light undergrowth.</p> | | | | | | | | | | | | | | | | |
| 0.80 | Dirt road, 15 lks. wide, bears N. 10° W. and S. 10° E. | | | | | | | | | | | | | | | | |
| 4.270 | Point for the E 1/16 sec. cor. of secs. 23 and 26. | | | | | | | | | | | | | | | | |
| <table border="1"> <tr> <td colspan="2" data-bbox="217 1415 390 1500" style="text-align: center;">UNION COUNTY SURVEYOR</td> </tr> <tr> <td data-bbox="217 1500 390 1585">Date Received</td> <td data-bbox="217 1500 390 1585">3/5/13</td> </tr> <tr> <td data-bbox="217 1585 390 1670">Date Filed</td> <td data-bbox="217 1585 390 1670">3/5/13</td> </tr> <tr> <td data-bbox="217 1670 390 1734">by</td> <td data-bbox="217 1670 390 1734">M. G. Miller</td> </tr> <tr> <td data-bbox="217 1734 390 1947">113-2013R</td> <td></td> </tr> </table> | UNION COUNTY SURVEYOR | | Date Received | 3/5/13 | Date Filed | 3/5/13 | by | M. G. Miller | 113-2013R | | <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: right;">S 23</td> </tr> <tr> <td style="text-align: right;">E 1/16</td> <td style="border-top: 1px solid black; text-align: right;">S 26</td> </tr> <tr> <td></td> <td style="text-align: right;">1991</td> </tr> </table> <p>from which</p> <p>A larch, 17 ins. diam., bears N. 35½° E., 82 lks. dist., mkd. E 1/16 S23 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 65½° E., 111 lks. dist., mkd. E 1/16 S26 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p> | | S 23 | E 1/16 | S 26 | | 1991 |
| UNION COUNTY SURVEYOR | | | | | | | | | | | | | | | | | |
| Date Received | 3/5/13 | | | | | | | | | | | | | | | | |
| Date Filed | 3/5/13 | | | | | | | | | | | | | | | | |
| by | M. G. Miller | | | | | | | | | | | | | | | | |
| 113-2013R | | | | | | | | | | | | | | | | | |
| | S 23 | | | | | | | | | | | | | | | | |
| E 1/16 | S 26 | | | | | | | | | | | | | | | | |
| | 1991 | | | | | | | | | | | | | | | | |