


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:
Corner not previously established.

T 4 S R 41 E Z-06



DESCRIPTION OF CORNER EVIDENCE FOUND:
None

See Survey Number 031-2012

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At position determined by survey, I set a 5/8"x30" iron pin with 2 1/2" aluminum cap, 30 inches in the ground, from which:

- A 6 inch Ponderosa Pine bears South 26° West, a distance of 71.25 feet, marked X BT.
- A 16 inch Ponderosa Pine bears North 9° West, a distance of 44.70 feet, marked W 1/16 S32 BT.

I set a steel fencepost 1 foot South of the corner monument.
I hereby certify that the corner was monumented on September 25, 2012.
Witness: Rick Robinson

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**



OREGON
June 2, 2010
JEFFERY S. HSU
83571

Renewal Date: June 30, 2013

BAGETT - GRIFFITH & BLACKMAN

T 4 S R 41 E

S 32

W 1/16

S 5

T 5 S

2012

PLS 83571

**UNION COUNTY
SURVEYOR**

Date Received 9/28/12

Date Filed 9/28/12

Filed By R. ROBINSON, DEPUTY

File Number 037-2012R

I used a steel tape and magnetic compass in the establishment of the accessories. I used 16° East declination, the distance to the bearing trees are to a 60d spike driven into the root crown at the right side of the tree. I place a brass washer marked OPLS 83571 in the lower blaze of the accessories.