Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

	CHAINS	
	36.870	Point for the % sec. cor. of secs. 3 and 4, at proportionate distance; there is no remaining evidence of the original corner.
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		T 5 S R 41 E
		S 4 S 3 1990
		from which
•		A ponderosa pine, 22 ins. diam., bears S. 85° E., 43 lks. dist., mkd. 1/4 S3 BT.
		A ponderosa pine, 18 ins. diam., bears S. 83° W., 80 lks. dist., mkd. 1/4 S4 BT.
		Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
		Continue along broken W. slope.
	54.30	Broad spur, slopes W.
	55.305	Point for the N 1/16 sec. cor. of secs. 3 and 4.
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
		N 1/16 S 4 S 3 1990
		from which
		A ponderosa pine, 15 ins. diam., bears S. 42½° E., 126 lks. dist., mkd. N 1/16 S3 BT.
		A ponderosa pine, 13 ins. diam., bears S. 1° E., 92 lks. dist., mkd. N 1/16 S4 BT.
		Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
		Descend steep NW. slope through medium timber and undergrowth to Little Catherine Creek; thence asc.
	73.840	The cor. of secs. 3, 4, 33, and 34 on the N. bdy. of the Tp.,
UNION	COUNTY	perpetuated from the original corner stone, no longer visible, and recorded by Duane I. Griffith, Oregon Registered Land Surveyor No. 644, in 1986, recorded under file No. 22-86, monumented with an
SURV	EYOR	aluminum post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 2½ ft. base, to top, with aluminum
Date Received	3/5/13	cap mkd.
Date Filed	3/5/13	
y All	6 Min	
No. OZ	25-7013R	