


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by H. Thatcher in 1879 under contract #320.
Set a 19x13x13 stone for 1/4 corner. Raised stone mound at corner.



Description of corner evidence found:

Found 19"x13"x13" stone with a poor 1/4 on the west face. Position fits calls to creek north & south. Found Valsetz K tag on 25" fir snag approx. 30' SW dated 1964. Tree has old blazes on north and south sides. I find no evidence of their corner position.

**UNION COUNTY
SURVEYOR**

Date Received 8-30-88
Date Filed 8-30-88
By G. LANGLITZ DEPUTY
File No. 110-88R

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the found original stone I set a 2 1/2" x 30" aluminum pipe with 2 1/2" aluminum cap 24" in ground to bed-rock in a mound of stone. Buried original stone upside down on west side of pipe.
A steel fence post with USFS 54-9 sign is 4' North.

T5S R41E
1/4
S51S4
1988
RLS 1664

Bearing trees:

- a 4" fir bears N60 1/2°W - 44.5' scribed "1/4S5BT" with brass tag stamped RLS 1664 in blaze
- a 9" fir bears S66 1/2°E - 41.3' scribed "1/4S4BT" with brass tag stamped RLS 1664 in blaze

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Carl E. Sundet

**OREGON
JULY 14, 1978
CARL E. SUNDET
1664**

Bearing trees have a 6" red band painted at breast height on smoothed bark and USFS 54-3 and 54-9 signs attached.

I hereby certify the above corner was perpetuated as herein described on July 21, 1988
Witness: R. Vaughn

Office of..... County of.....
State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....
..... by
(COUNTY OFFICIAL) (DEPUTY)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
22.05	Track road, 15 lks. wide, bears N. and S.
22.95	Ravine, drains N.
24.85	Spur, slopes N.; desc. NW. slope.
40.730	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9 at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div data-bbox="815 623 1020 751" style="text-align: center;"> <p>T 5 S R 41 E S 4 $\frac{1}{4}$ ————— S 9 1990</p> </div> from which A larch, 9 ins. diam., bears N. 64° E., 33 lks. dist., mkd. $\frac{1}{4}$ S4 BT. A larch, 20 ins. diam., bears S. 9° W., 98 lks. dist., mkd. $\frac{1}{4}$ S9 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Continue along broken N. slope through medium timber and undergrowth.
81.460	The cor. of secs. 4, 5, 8, and 9. <hr/> N. $0^\circ 12' 00''$ W., bet. secs. 4 and 5. Ascend S. slope through medium timber and light undergrowth.
4.50	Descend steep N. slope to Little Catherine Creek; thence ascend.
38.80	Stream, 5 lks. wide, course S. 10° E.
39.930	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, perpetuated from original corner stone, no longer visible, and recorded by Carl E. Sundet, Oregon Registered Land Surveyor No. 1664, in 1988, recorded under file No. 110-88R, monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with aluminum cap mkd. <div data-bbox="824 1613 1029 1740" style="text-align: center;"> <p>T 5 S R 41 E S 5 S 4 1988 RLS 1664</p> </div> from which bearing trees mkd. by Sundet

UNION COUNTY SURVEYOR	
Date Received	<u>3/5/13</u>
Date Filed	<u>3/5/13</u>
By	<u><i>Rich G. Munn</i></u>
File No.	<u>027-2013R</u>

480

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A fir, 10 ins. diam., bears S. 70° E., 62 lks. dist., with scribe marks $\frac{1}{4}$ S4 BT on open blaze.</p> <p>A fir, 5 ins. diam., bears N. 62½° W., 67 lks. dist., with scribe marks $\frac{1}{4}$ S5 BT on open blaze.</p>
1.00	<p>N. 0° 32' 30" E., beginning new measurement.</p> <p>Stream, 5 lks. wide, course S. 20° W.; continue along streambed.</p>
5.00	<p>Ascend SW. slope, through medium timber and light undergrowth.</p>
35.815	<p>The cor. of secs. 4, 5, 32, and 33 on the N. bdy. of the Tp., reestablished by proportionate measurement and recorded by Duane L. Griffith, Oregon Registered Land Surveyor No. 644, in 1986, recorded under file No. 22-86. There is no remaining evidence of the original corner; therefore, this position is accepted as the corner, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 20 ins. above ground, and in a mound of stone, 3½ ft. base, to top, with aluminum cap mkd.</p>
	<p style="text-align: center;">BAGETT GRIFFITH ASSOC T 4 S R 41 E S 32 S 33 S 5 S 4 T 5 S 1986 OPLS 644</p>
	<p>from which bearing trees mkd. by Griffith</p>
	<p>A ponderosa pine, 15 ins. diam., bears N. 59° E., 35 lks. dist., with fragmentary scribe marks on partially healed double blaze.</p>
Date Received 3/5/13	<p>A Douglas fir, 20 ins. diam., bears S. 84° E., 84 lks. dist., with scribe marks T5S R41E S4 BT on open double blaze.</p>
Date Filed 3/5/13	<p>A Douglas fir, 12 ins. diam., bears S. 55° W., 92 lks. dist., with pitched over double blaze.</p>
By <i>R. L. Griffith</i>	<p>A ponderosa pine, 8 ins. diam., bears N. 40° W., 15½ lks. dist., with pitched over double blaze.</p>
File No. 027-2013R	<p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 5 and 32 on the N. bdy. of the Tp., perpetuated from the original corner stone, no longer visible, and recorded by Duane I. Griffith, Oregon Registered Land Surveyor No. 644, in 1986, recorded under file No. 22-86, bears N. 89° 51' 00" W., 38.310 chs. dist., monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above a mound of stone, 3 ft. base, to top, with aluminum cap mkd.</p>

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By *R. L. Griffith*

File No. 027-2013R