

Subdivision of Section 4,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>BAGETT GRIFFITH ASSOC T 4 S R 41 E S 33 $\frac{1}{4}$ S 4 T 5 S 1986 PLS 644</p>
	<p>from which bearing trees mkd. by Griffith</p> <p>A fir, 12 ins. diam., bears N. 46° E., 22 lks. dist., with fragmentary scribe marks on partially healed double blaze.</p> <p>A larch, 9 ins. diam., bears S. 6° W., 89 lks. dist., with healed double blaze.</p>
	<p>From this point, the cor. of secs. 3, 4, 33, and 34, bears S. 89° 50' 30" E., 38.305 chs. dist., hereinbefore described.</p>
	<p>From this same point, the cor. of secs, 4, 5, 32, and 33, bears N. 89° 50' 00" W., 38.305 chs. dist., hereinbefore described.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.</p>
	<p>N. 89° 04' 00" W., on the E. and W. center line of sec. 4.</p>
	<p>Descend broken W. slope, through medium timber and undergrowth.</p>
19.780	<p>Point for the center E 1/16 sec. cor. of sec. 4.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E 1/16 C $\frac{1}{16}$ C S 4 1991</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N. 17° E., 10 lks. dist., mkd. CE 1/16 S4 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 65° W., 24 lks. dist., mkd. CE 1/16 S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a broad spur, sloping S. 65° W.</p>
37.45	<p>Stream, 25 lks. wide, course SW.</p>
39.25	<p>Dirt road, 20 lks. wide, bears N. and S.</p>
39.560	<p>The center $\frac{1}{4}$ sec. cor. of sec. 4.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>M. G. Miller</i>
File No.	029-2013R