452

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	From this point, triangulation station "CATH," established by the United States Forest Service in 1989, bears N. 44° 26′ 20" W., 16.530 chs. dist., monumented with an aluminum cap, firmly set on an aluminum rod, projecting 3 ins. above ground, with top mkd. USFS CATH 1989 and a triangle.
	From the ¼ sec. cor. of secs. 2 and 11, monumented with the original unmarked slate stone, 18 x 12 x 2 ins. (record, 16 x 11 x 5 ins.), firmly set 8 ins. in the ground.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 5 S R 41 E S 2 S 11
	1990
UNION COUNTY	from which new bearing trees
SURVEYOR	A lodgepole pine, 12 ins. diam., bears N. 6° E., 45 lks. dist., mkd. ¼ S2 BT.
Date Received 35/13	A lodgepole pine, 8 ins. diam., bears S. 55° W., 11½/lks. dist., mkd. ¼ S11 BT.
Date Filed 3/5/13	Deposit a white "DEEP-1" magnetic marker at the base and the
By M. Gler	corner stone alongside the stainless steel post. N. 88° 33′ 00" W., bet. secs. 2 and 11.
File No. 032-2013R	Over broken land through dense timber and light undergrowth.
39.925	The cor. of secs. 2, 3, 10, and 11.
	N. 0° 21' 00" W., bet. secs. 2 and 3.
	Along rolling ridgetop changing to NE. slope, through heavy timber and light undergrowth.
39.930	The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented with the original slate stone, 14 x 8 x 5 ins. (record, 14 x 10 x 6 ins.), loosely set 2 ins. in the ground, with chisel marks 1/ on the E. face.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.
	T 5 S R 41 E
	s 3
	from which new bearing trees

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

. [GUADIO	
	CHAINS	1
		A lodgepole pine, 8 ins. diam., bears N. 43° E., 25 lks. dist., mkd. ½ S2 BT.
		A larch, 10 ins. diam., bears N. 15° W., 30 lks. dist., mkd. 4 S3 BT.
		Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.
		N. 3° 57' 00" W., beginning new measurement.
		Descend NE. slope to Little Catherine Creek; thence asc. broken SW. slope.
	34.110	The cor. of secs. 2, 3, 34, and 35 on the N. bdy. of the Tp., perpetuated and recorded by Duane I. Griffith, Oregon Registered Land Surveyor No. 644, in 1986, recorded under file No. 22-86, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, in a collar of stone, with aluminum cap mkd.
		BAGETT GRIFFITH AND ASSOC T 4 S R 41 E S 34 S 35 S 3 S 2 T 5 S 1986 OPLS 644
		from which the remains of the original bearing trees
		A ponderosa pine, 42 ins. diam., bears S. 8° E., 44 lks. dist., with axe marks on open blaze.
		A root hole, bears S. 85° W., 18 lks. dist., with pine log alongside, 30 ins. diam., with open, rotted blaze.
UNION	COUNTY	A root hole, bears N. 80° W., 16 lks. dist.
SUR'	/EYOR	and bearing trees mkd. by Griffith
Date Received	3/5/13	A larch, 12 ins. diam., bears N. 59° E., 62 lks. dist., with scribe marks 4S R41E S35 BT on open, double blaze.
Date Filed	3/5/13	A larch, 10 ins. diam., bears S. 42° W., 59 lks. dist., with scribe marks T5S R41E S3 BT on open, double blaze.
cy Nich	G. Mun	A larch, 9 ins. diam., bears N. 18° W., 38 lks. dist., with scribe marks T4S R41E S34 BT on open, double blaze.
File No	32-2013R	From the standard cor. of secs. 33 and 34 on the S. bdy. of the
	omatorio programa de la companya del companya de la companya del companya de la c	Tp.
		N. 1° 48' 00" E., bet. secs. 33 and 34.
		Ascend SE. slope along decrepit wire fence.
	10.00	Descend NE. slope through logged area.
		4