

CERTIFIED RECORD OF LAND CORNER MONUMENTATION


E-4

East 1/16 Section Corner of Sections 6 & 7, T.5S., R.41E., W.M.

History of original corner establishment:

1991, Philip G. Griffin, Cadastral Surveyor, BLM, conducted a dependent resurvey in this township and established this corner, his record states:

“Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.” (as shown in the diagram),



“from which

- A ponderosa pine, 10 ins. diam., bears N. 64° E., 47 lks. dist., mkd. E 1/16 S6 BT.
- A ponderosa pine, 10 ins. diam., bears S. 77° W., 19 1/2 lks. dist., mkd. E 1/16 S7 BT.”

Description of corner evidence found:

Found a stainless steel post, 2 1/2 ins. diam., 12 ins. above the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd. as shown in the diagram,

from which

- A ponderosa pine, 10 ins. diam. snag, 3 1/2 ft. high, bears N. 64° E., 31.2 ft. dist. (31.0 ft. Griffin), with scribe marks “E 1/16 S6 BT” visible.
- A ponderosa pine, 10 ins. diam., bears S. 77° W., 12.4 ft. dist. (12.9 ft. Griffin), with scribe marks “E 1/16 S7 BT” visible.

Description of monument and accessories I established to perpetuate the original location of this corner:

From the brass cap, I established the following references:

A ponderosa pine, 7 ins. diam., bears N. 61° E., 31.7 ft. dist., marked X, at breast height and BT, in a low blaze, with a brass washer marked LS 2211, nailed between the B & T.

I set a galvanized steel post, Easterly on the property line, 3-5 ft. dist., with a Property Boundary sign attached, I also set a galvanized steel post, Westerly on the property line, 3-5 ft. dist., with a Property Boundary & a Land Survey Monument sign attached.

There is a barbed wire fence, 12 feet south of this corner, extending east & west. There is also a smooth wire fence, 234 feet east of this corner, extending to the north from the barbed wire fence (the fence corner is 2 ft. south of the section line).

I hereby certify that the above corner was perpetuated by me and my crew on June 9, 1998.

Compass declination used 18 1/2° East.

See also, filed survey plat.

Witnessed by crew member: Roanna K. Tomlinson

**UNION COUNTY
SURVEYOR**

Date Received 8/5/98

Date Filed 8/29/98

By R. ROBINSON, DKS/M

File No. 060-1998R

**REGISTERED
PROFESSIONAL
LAND SURVEYOR**

Roger O. Green

**OREGON
JULY 17, 1986
ROGER O. GREEN
2211**

JUL 29 1998

Current registration
period ends 6-30-99.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	Descend over SW. slope, along wire fence through medium timber and undergrowth.
20.080	<p>Point for the E 1/16 sec. cor. of secs. 6 and 7.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 6 E 1/16 ——— S 7 1990</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 64° E., 47 lks. dist., mkd. E 1/16 S6 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 77° W., 19½ lks. dist., mkd. E 1/16 S7 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located 18 lks. N. of a barbed wire fence, extending E. and W.</p>
22.30	Ravine, drains S.; asc. gradual SE. slope.
34.80	Descend SW. slope.
40.160	<p>The ¼ sec. cor. of secs. 6 and 7, perpetuated from the original corner stone, no longer visible, and recorded by William W. Briggs, Registered Professional Engineer No. 3780, in 1975, recorded under file No. 715-84R, monumented with a brass cap, 3 ins. diam., firmly set in concrete, with top mkd.</p> <div style="text-align: center;"> <p>S 6 ¼ ——— S 7 SET BY WWB RPE 3780</p> </div>
	<p>from which the remains of bearing trees mkd. by Briggs</p> <p style="padding-left: 40px;">A sawed pine stump, 13 ins. diam., bears N. 18° E., 42 lks. dist., with scribe marks S6 BT on loose piece of wood alongside.</p> <p style="padding-left: 40px;">A ponderosa pine, 22 ins. diam., bears S. 76½° E., 66 lks. dist., with scribe marks S7 BT legible on pitched over blaze.</p> <p>and a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. 26° E., 88 lks. dist., mkd. ¼ S6 BT.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>W. H. G. Miller</i>
File No.	035-2013R