


CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

Corner established by H. Thatcher in 1879 under contract #320.

Set a basalt stone 14x12x6 for corner, raised stone mound at corner.



Description of corner evidence found:

Found 14"x12"x6" stone marked with 5 grooves south and 4 notches east in a mound of stone. Alongside was buried a 1" pipe with washer stamped CX11 1973.

UNION COUNTY SURVEYOR	
Date Received	<u>8-30-88</u>
Date Filed	<u>8-30-88</u>
By	<u>G. LANGLITZ, Deputy</u>
File No.	<u>109-88 R</u>

Description of monument and accessories I established to perpetuate the original location of this corner:

At the position of the found original stone I set a 2 1/2" x30" aluminum pipe with 2 1/2" aluminum cap 14" in ground to bed-rock in large mound of stone. Buried original stone upside down on NE side of pipe. Buried 1" pipe south of aluminum pipe.

T 5S R41E
S5	S4
 S8 | S9
 1988
 RLS 1664

Bearing trees:

- a 4" ponderosa pine bears N42 1/4°W - 48.5' scribed "X BT" with brass tag stamped RLS 1664 in blaze
- a 8" ponderosa pine bears N53 3/4°E - 21.0' scribed "T5SR41ES4BT" with brass tag stamped RLS 1664 in blaze
- a 6" ponderosa pine bears S61 3/4°E - 62.0' scribed "T5SR41ES9BT" with brass tag stamped RLS 1664 in blaze
- a 9" ponderosa pine bears S46 1/2°W - 12.0' scribed "T5SR41ES8BT" with brass tag stamped RLS 1664 in blaze

REGISTERED PROFESSIONAL LAND SURVEYOR	
<i>Carl E. Sundet</i>	
OREGON JULY 14, 1978 CARL E. SUNDET 1664	

Bearing trees have a 6" red band painted at breast height on smoothed bark and USFS 54-3 and 54-9 signs attached

I hereby certify the above corner was perpetuated as herein described on July 20, 1988.

Witness: R. Vaughn


Office of..... County of.....

State of....., I hereby certify that the within instrument was filed in this office for record on the..... day of....., 19.....

..... by
(COUNTY OFFICIAL) (DEPUTY)

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

E-9



History of original corner establishment:

SURVEYED BY: S. ALBRIGHT, 1971, CONTRACT NO. 350

The cor. of secs. 4, 5, 8 and 9, determined at record bearing from remaining original bearing trees:

A western larch snag, 11 ins. in diam., bears N.70°E., 14lks. dist., with scribe marks T6S 41E S4 BT visible on open double blaze. (Record, 11 lks.)

A sawed western larch stump, 17 ins. in diam., bears S.35°E., 26 1/2 lks. dist., with scribe marks BT visible on open blaze. (Record, 14 lks.)

A white fir, 18 ins. in diam., bears S.57°W., 16 lks. dist., with scribe mark 8 visible on open blaze. (Record, 16lks.)

at the corner point

set an iron post, 28 ins. long, 2 1/2" in diam., 24" in the ground, with brass cap

from which new bearing trees

- A white fir, 18" diam., bears N.24 1/2°E., 38 lks. dist. mkd. T6S R41E S4 BT
- A western larch, 10" diam., bears S.17°E., 114 lks. dist. mkd. T6S R41E S9 BT
- A fir, 9" diam., bears S.74°W., 44 lks. dist. mkd. T6S R41E S8 BT
- A white fir, 16" diam., bears N.72°W., 312 lks. dist. mkd. T6S R41E S5 BT

Description of corner evidence found:

Found a 3" B.L.M. bass cap, cap marked per diagram, 6 " above the ground, with no stones, from which:

- A dead fir, 28" diam., bears N.21°36'E., 24.53', with a 19" healed blaze.
- A western larch, 15" diam., bears S.20°06'E., 75.67', with a 24" healed blaze.
- A fir, 15" diam., bears S.72°46'W., 29.20', with a 15" healed blaze.
- A fir, 20" diam., bears N.74°22'W., 206.61', with a 24" healed blaze.

Description of monument and accessories I established to perpetuate the original location of this corner:

A stump, 26" diam., 39 ins. high, with a 1/2" rebar set 6" above the middle of stump, with a aluminum cap bears N.10°22'E., 15.90'.

REFERENCE: RECORD OF SURVEY, LONGSHOT CADASTRAL SURVEY
WITNESS TO MONUMENT: DAVID SUTHERLAND
BEARINGS TAKEN TO BRASS TAG AT CENTER OF BLAZE, DISTANCES MEASURED TO BRASS TAG ON SIDE CENTER OF TREE. OBSERVED WITH ELECTRONIC TOTAL STATION AND STEEL TAPE.
BASIS OF BEARING WAS GEODETIC BEARING DETERMINED FROM GPS OBSERVATIONS.

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was filed in this office
for record on the ____ day of _____, 19____
_____ by
(COUNTY OFFICIAL) (DEPUTY)
AG

UNION COUNTY SURVEYOR

Date Received 11/14/06

Date Filed 9/9/06

R. ROBINSON, Deputy

No. 007-2006R

REGISTERED PROFESSIONAL LAND SURVEYOR

M & Stoll S/OS

OREGON
JULY 15, 1983
RONALD E. STOLL
2058

478

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

39.835

The cor. of secs. 4, 5, 8, and 9, perpetuated from the original corner stone, no longer visible, and recorded by Carl E. Sundet, Oregon Registered Land Surveyor No. 1664, in 1988, recorded under file No. 109-88R, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 14 ins. above ground, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd.

T 5 S R 41 E
S 5 | S 4
S 8 | S 9
1988
RLS 1664

from which bearing trees mkd. by Sundet

A ponderosa pine, 9 ins. diam, bears N. 52° E., 31½ lks. dist., with scribe marks T5S R41E S4 BT on open blaze.

A ponderosa pine, 8 ins. diam., bears S. 65° E., 94 lks. dist., with scribe marks T5S R41E S9 BT on open blaze.

A ponderosa pine, 10 ins. diam., bears S. 42° W., 18½ lks. dist., with pitched over blaze.

A ponderosa pine, 5 ins. diam., bears N. 43° W., 73½ lks. dist., with scribe marks X BT on open blaze.

From this point, the corner of wire fences, extending E. and S., bears N. 31° E., 0.430 chs. dist.

From the cor. of secs. 3, 4, 9, and 10.

S. 88° 41' 00" W., bet. secs. 4 and 9.

Along gradual N. slope through medium timber and undergrowth.

10.35

Graveled road, 20 lks. wide, bears N. 20° E. and S. 20° W., in a curve; desc. NW. slope.

20.365

Point for the E 1/16 sec. cor. of secs. 4 and 9.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

E 1/16 S 4
S 9
1990

from which

A Douglas fir, 22 ins. diam., bears N. 49° E., 8 lks. dist., mkd. E 1/16 S4 BT.

A Douglas fir, 20 ins. diam., bears S. 69° W., 43 lks. dist., mkd. E 1/16 S9 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

[Signature]

File No.

C37-2013R