479

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAIN	NS
22.05	Track road, 15 lks. wide, bears N. and S.
22.95	
24.85	
40.73	Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 9 at proportionate distance; there is no remaining evidence of the original corner.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 5 S R 41 E S 4
	S 9 1990
	from which
	A larch, 9 ins. diam., bears N. 64° E., 33 lks. dist., mkd. $\frac{1}{4}$ S4 BT.
	A larch, 20 ins. diam., bears S. 9° W., 98 lks. dist., mkd. ¼ S9 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue along broken N. slope through medium timber and undergrowth.
81.46	O The cor. of secs. 4, 5, 8, and 9.
	N (28 124 201 F)
	N. 0° 12' 00" W., bet. secs. 4 and 5.
	Ascend S. slope through medium timber and light undergrowth.
4.50	
38.80	Stream, 5 lks. wide, course S. 10° E.
39.93	stone, no longer visible, and recorded by Carl E. Sundet, Oregon Registered Land Surveyor No. 1664, in 1988, recorded under file
UNION COUNTY SURVEYOR	No. 110-88R, monumented with an aluminum post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 12 ins. above ground, and in a mound of stone, $3\frac{1}{2}$ ft. base, to top, with aluminum cap mkd.
As committee to a control of the con	T 5 S R 41 E
Date Received 3/5/	S 5 S 4
Date Filed 3/5/	1988 RLS 1664
ey Mahlun	from which bearing trees mkd. by Sundet
400	113 P
File No. 038-20	