

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS 39.835	The cor. of secs. 4, 5, 8, and 9, perpetuated from the original corner stone, no longer visible, and recorded by Carl E. Sundet, Oregon Registered Land Surveyor No. 1664, in 1988, recorded under file No. 109-88R, monumented with an aluminum post, 2½ ins. diam., firmly set, projecting 14 ins. above ground, and in a mound of stone, 4 ft. base, to top, with aluminum cap mkd. <div style="text-align: center; margin: 10px 0;"> <table border="0"> <tr> <td>T 5 S</td> <td>R 41 E</td> </tr> <tr> <td>S 5</td> <td>S 4</td> </tr> <tr> <td>S 8</td> <td>S 9</td> </tr> <tr> <td colspan="2">1988</td> </tr> <tr> <td colspan="2">RLS 1664</td> </tr> </table> </div> from which bearing trees mkd. by Sundet <ul style="list-style-type: none"> A ponderosa pine, 9 ins. diam, bears N. 52° E., 31½ lks. dist., with scribe marks T5S R41E S4 BT on open blaze. A ponderosa pine, 8 ins. diam., bears S. 65° E., 94 lks. dist., with scribe marks T5S R41E S9 BT on open blaze. A ponderosa pine, 10 ins. diam., bears S. 42° W., 18½ lks. dist., with pitched over blaze. A ponderosa pine, 5 ins. diam., bears N. 43° W., 73½ lks. dist., with scribe marks X BT on open blaze. From this point, the corner of wire fences, extending E. and S., bears N. 31° E., 0.430 chs. dist.	T 5 S	R 41 E	S 5	S 4	S 8	S 9	1988		RLS 1664	
T 5 S	R 41 E										
S 5	S 4										
S 8	S 9										
1988											
RLS 1664											
10.35	From the cor. of secs. 3, 4, 9, and 10. S. 88° 41' 00" W., bet. secs. 4 and 9. Along gradual N. slope through medium timber and undergrowth.										
20.365	Graveled road, 20 lks. wide, bears N. 20° E. and S. 20° W., in a curve; desc. NW. slope. <p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center; margin: 10px 0;"> <table border="0"> <tr> <td>E 1/16</td> <td>S 4</td> </tr> <tr> <td></td> <td>S 9</td> </tr> <tr> <td></td> <td>1990</td> </tr> </table> </div> from which <ul style="list-style-type: none"> A Douglas fir, 22 ins. diam., bears N. 49° E., 8 lks. dist., mkd. E 1/16 S4 BT. A Douglas fir, 20 ins. diam., bears S. 69° W., 43 lks. dist., mkd. E 1/16 S9 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.	E 1/16	S 4		S 9		1990				
E 1/16	S 4										
	S 9										
	1990										

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>[Signature]</i>
File No.	039-2013R