Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

	CHAINS	A ponderosa pine, 12 ins. diam., bears S. 23° W., 5 lks. dist., mkd. ½ S9 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. Descend NE. slope through medium timber and light undergrowth. Top of ascent, ridgetop slopes W.
	79.360	The cor. of secs. 3, 4, 9, and 10, determined at the center of a flat mound of stone, 4 ft. diam.; loose alongside find the
		original slate stone, 16 x 12 x 5 ins. (record, 16 x 12 x 8 ins.), with two blunt notches on the top.
10 July 20 11		At the corner point
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.
		T 5 S R 41 E S 4 S 3 S 9 S 10 1990
		from which new bearing trees
		A ponderosa pine, 16 ins. diam., bears N. 67° E., 73 lks. dist., mkd. T5S R41E S3 BT.
		A ponderosa pine, 18 ins. diam., bears S. 65° E., 94 lks. dist., mkd. T5S R41E S10 BT.
		A ponderosa pine, 14 ins. diam., bears S. 67° W., 40 lks. dist., mkd. T5S R41E S9 BT.
		A ponderosa pine, 12 ins. diam., bears N. 74° W., 70 lks. dist., mkd. T5S R41E S4 BT.
		Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.
	^	From the cor. of secs. 2, 3, 10, and 11.
		s. 89° 19' 00" W., bet. secs. 3 and 10.
		Descend W. slope, through logged area. Date Received 3/5/13
	9.75	Graveled road, 20 lks. wide, bears N. and S. Date Filed 3/5//3
	18.25	Same graveled road, 20 lks. wide, bears NW. and SE.
	19.880	Point for the E 1/16 sec. cor. of secs. 3 and 10. By M.C., Mhr.
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diffe No. 22 ins. 040-2013 R in the ground, with brass cap mkd.
	(_C	