

465

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS							
	<p>A ponderosa pine, 12 ins. diam., bears S. 23° W., 5 lks. dist., mkd. ¼ S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Descend NE. slope through medium timber and light undergrowth.</p>						
77.80	Top of ascent, ridgetop slopes W.						
79.360	<p>The cor. of secs. 3, 4, 9, and 10, determined at the center of a flat mound of stone, 4 ft. diam.; loose alongside find the original slate stone, 16 x 12 x 5 ins. (record, 16 x 12 x 8 ins.), with two blunt notches on the top.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <table border="1"> <tr> <td>T 5 S</td> <td>R 41 E</td> </tr> <tr> <td>S 4</td> <td>S 3</td> </tr> <tr> <td>S 9</td> <td>S 10</td> </tr> </table> <p>1990</p> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 16 ins. diam., bears N. 67° E., 73 lks. dist., mkd. T5S R41E S3 BT.</p> <p>A ponderosa pine, 18 ins. diam., bears S. 65° E., 94 lks. dist., mkd. T5S R41E S10 BT.</p> <p>A ponderosa pine, 14 ins. diam., bears S. 67° W., 40 lks. dist., mkd. T5S R41E S9 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears N. 74° W., 70 lks. dist., mkd. T5S R41E S4 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>	T 5 S	R 41 E	S 4	S 3	S 9	S 10
T 5 S	R 41 E						
S 4	S 3						
S 9	S 10						
	<p>From the cor. of secs. 2, 3, 10, and 11.</p> <p>S. 89° 19' 00" W., bet. secs. 3 and 10.</p> <p>Descend W. slope, through logged area.</p>						
9.75	Graveled road, 20 lks. wide, bears N. and S.						
18.25	Same gravelled road, 20 lks. wide, bears NW. and SE.						
19.880	<p>Point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>						

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By M. G. [Signature]

File No. 042-2013R

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<div style="text-align: right;"> S 3 E 1/16 <hr style="width: 50px; display: inline-block; vertical-align: middle;"/> S 10 1990 </div> <p>from which</p> <p>A lodgepole pine, 10 ins. diam., bears N. 26° E., 18 lks. dist., mkd. E 1/16 S3 BT.</p> <p>A larch, 16 ins. diam., bears S. 42° W., 84 lks. dist., mkd. E 1/16 S10 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
21.15	Graveled road, 20 lks. wide, bears N. 80° E. and S. 60° W., in a curve.
32.75	Same gravelled road, 20 lks. wide, bears N. 30° W. and S. 30° E.; desc. broken W. slope through logged area.
39.760	Point for the 1/4 sec. cor. of secs. 3 and 10 at proportionate distance; there is no remaining evidence of the original corner. Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: right;"> T 5 S R 41 E S 3 1/4 <hr style="width: 50px; display: inline-block; vertical-align: middle;"/> S 10 1990 </div>
	<p>from which</p> <p>A larch, 18 ins. diam., bears N. 79° E., 36 lks. dist., mkd. 1/4 S3 BT.</p> <p>A larch, 9 ins. diam., bears S. 74° W., 33 lks. dist., mkd. 1/4 S10 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
79.520	<p>Descend NW. slope changing to W. slope and SW. slope, through logged area.</p> <p>The cor. of secs. 3, 4, 9, and 10.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>N. 3° 34' 00" W., bet. secs. 3 and 4.</p> <p>Descend gradual NW. slope.</p>
1.50	Graveled road, 25 lks. wide, bears N. 30° E. and S. 50° W., in a curve; continue along broken W. slope through medium timber and undergrowth.

UNION COUNTY SURVEYOR	
Date Received	<u>3/5/13</u>
Date Filed	<u>3/5/13</u>
By	<u><i>M. L. G. Blum</i></u>
File No.	<u>042-2013R</u>