

452

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	<p>From this point, triangulation station "CATH," established by the United States Forest Service in 1989, bears N. 44° 26' 20" W., 16.530 chs. dist., monumented with an aluminum cap, firmly set on an aluminum rod, projecting 3 ins. above ground, with top mkd. USFS CATH 1989 and a triangle.</p>
	<p>From the ¼ sec. cor. of secs. 2 and 11, monumented with the original unmarked slate stone, 18 x 12 x 2 ins. (record, 16 x 11 x 5 ins.), firmly set 8 ins. in the ground.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 2 ¼ ——— S 11 1990</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A lodgepole pine, 12 ins. diam., bears N. 6° E., 45 lks. dist., mkd. ¼ S2 BT.</p> <p style="padding-left: 40px;">A lodgepole pine, 8 ins. diam., bears S. 55° W., 11½ lks. dist., mkd. ¼ S11 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>
39.925	<p>N. 88° 33' 00" W., bet. secs. 2 and 11.</p> <p>Over broken land through dense timber and light undergrowth.</p> <p>The cor. of secs. 2, 3, 10, and 11.</p>
39.930	<p>N. 0° 21' 00" W., bet. secs. 2 and 3.</p> <p>Along rolling ridgetop changing to NE. slope, through heavy timber and light undergrowth.</p> <p>The ¼ sec. cor. of secs. 2 and 3, monumented with the original slate stone, 14 x 8 x 5 ins. (record, 14 x 10 x 6 ins.), loosely set 2 ins. in the ground, with chisel marks 1/ on the E. face.</p>
<p>UNION COUNTY SURVEYOR</p> <p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/13</u></p> <p>By <u>R. G. [Signature]</u></p> <p>File No. <u>044-2013R</u></p>	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 3 ¼ S 2 1990</p> <p>from which new bearing trees</p>