

501

Subdivision of Section 10,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS  59.485	Point for the center N 1/16 sec. cor. of sec. 10.  Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in a drill hole on the SW. portion of a boulder, 12 ft. x 9 ft. x 8 ft., with top mkd.  $\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad   \quad \text{S } 10 \\ \text{C} \\ 1991 \end{array}$ from which  A Douglas fir, 16 ins. diam., bears N. 35° E., 11 lks. dist., mkd. CN 1/16 S10 BT.  A ponderosa pine, 15 ins. diam., bears S. 7° E., 14 lks. dist., mkd. CN 1/16 S10 BT.
79.390	Continue along W. slope, through logged area.  The ¼ sec. cor. of secs. 3 and 10.
16.05	From the ¼ sec. cor. of secs. 10 and 11. S. 89° 28' 30" W., on the E. and W. center line of sec. 10. Descend W. slope, through logged area.
19.805	Dirt road, 15 lks. wide, bears N. and S.  Point for the center E 1/16 sec. cor. of sec. 10.  Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  $\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \text{---} \quad \text{C} \\ \text{S } 10 \\ 1991 \end{array}$ from which  A ponderosa pine, 14 ins. diam., bears S. 60° E., 6 lks. dist., mkd. CE 1/16 S10 BT.  A larch, 16 ins. diam., bears S. 19° W., 57 lks. dist., mkd. CE 1/16 S10 BT.
39.610	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.  Continue to descend W. slope changing to SW. slope.  The center ¼ sec. cor. of sec. 10.
50.60	Graveled road, 20 lks. wide, bears N. 65° W. and SE., in a curve.
64.35	Dirt road, 20 lks. wide, bears NW. and SE.

<b>UNION COUNTY SURVEYOR</b>	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>ALG</i>
File No.	046-2013R