

Subdivision of Section 10,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
73.50	Ascend E. slope.
79.480	The ¼ sec. cor. of secs. 9 and 10.
	<hr/>
	From the center E 1/16 sec. cor. of sec. 10.
	N. 0° 17' 00" W., on the N. and S. center line of the NE¼ of sec. 10.
	Along W. slope, through medium timber and light undergrowth.
11.50	Ravine, drains SW.; asc. over SE. slope, along E. edge of logged area.
19.930	Point for the NE 1/16 sec. cor. of sec. 10 at intersection with the E. and W. center line of the NE¼.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	NE 1/16 S 10 1991
	from which
	A spruce, 9 ins. diam., bears S. 34° E., 26 lks. dist., mkd. NE 1/16 S10 BT.
	A lodgepole pine, 22 ins. diam., bears N. 21° W., 38 lks. dist., mkd. NE 1/16 S10 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Ascend S. slope along E. edge of logged area.
25.00	Descend N. slope along E. edge of logged area.
39.860	The E 1/16 sec. cor. of secs. 3 and 10.
	<hr/>
	From the N 1/16 sec. cor. of secs. 10 and 11.
	S. 89° 24' 00" W., on the E. and W. center line of the NE¼ of sec. 10.
	Along broken N. slope changing to W. slope, through medium timber and light undergrowth.
17.10	Dirt road, 15 lks. wide, bears N. 20° E. and S. 20° W.
19.25	Ravine, drains S.
19.840	The NE 1/16 sec. cor. of sec. 10.
20.25	Track road, 10 lks. wide, bears N. and S.; asc. SE. slope through logged area.
27.75	Descend SW. slope.

**UNION COUNTY
SURVEYOR**

Date Received 3/5/13

Date Filed 3/5/13

By A. J. Gilman

File No. 047-2013R