## Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

		1. 5 S., R. 41 E., WIIIamette Melitian, Olegon
ſ	CHAINS	
		Along ridgetop through medium timber and undergrowth.
	17.00	Descend NE. slope.
e la company	19.965	Point for the N 1/16 sec. cor. of secs. 10 and 11.
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
		N 1/16 S 10   S 11 1990
		from which
		A spruce, 19 ins. diam., bears N. 80° E., 14 lks. dist., mkd. N 1/16 S11 BT.
	₹5	A larch, 13 ins. diam., bears N. 15° W., 99 lks. dist., mkd. N 1/16 S10 BT.
		Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
		Continue to descend NE. slope changing to SW. slope and W. slope.
	39.930	Point for the cor. of secs. 2, 3, 10, and 11 at proportionate distance; there is no remaining evidence of the original corner.
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
		T 5 S R 41 E  S 3   S 2  S 10   S 11  1990
		from which
	COUNTY VEYOR	A larch, 15 ins. diam., bears N. 7½° E., 121 lks. dist., mkd. T5S R41E S2 BT.
Date Received	3/5/13	A lodgepole pine, 15 ins. diam., bears S. 70° E., 69 lks. dist., mkd. T5S R41E S11 BT.
Date Filed	3/5/13	The marks BXO on the N. end of a rock outcrop, 8½ ft. long, 2½ ft. wide, 5 ft. high, bear S. 9° W., 33 lks. dist.
By JULI	Mlini	A lodgepole pine, 12 ins. diam., bears N. 30° W., 43 lks. dist., mkd. T5S R41E S3 BT.
File No	48-2013R	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
		The corner is located on a ridgetop, bearing N. and S.