Subdivision of Section 9, T. 5 S., R. 41 E., Willamette Meridian, Oregon

		It b bi, it is bi, williamout wellardin, oregon
	CHAINS	
	35.00	Top of ascent, along westerly slope on top of mountain.
	39.110	Point for the center $\frac{1}{4}$ sec. cor. of sec. 9, at intersection with the E. and W. center line.
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
		T 5 S R 41 E C ¹ 4 S 9 1991
		from which
		A larch, 15 ins. diam., bears S. 0½° W., 61 lks. dist., mkd. C½ S9 BT.
		A ponderosa pine, 15 ins. diam., bears S. 85° W., 42 lks. dist., mkd. C4 S9 BT.
		Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
		Continue along westerly slope.
	44.00	Descend NE. slope.
	72.00	Track road, 15 lks. wide, bears irregularly NW. and SE.
	78.870	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
		From the 1/4 sec. cor. of secs. 9 and 10.
		S. 88° 36' 00" W., on the E. and W. center line of sec. 9.
		Ascend E. slope.
	4.25	Ridge, bears N. and S.; desc. W. slope.
	20.145	Point for the center E 1/16 sec. cor. of sec. 9.
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
		c E 1/16
		s 9
		1991
UNION	COUNTY	from which
	EYOR	A fir, 12 ins. diam., bears N. 7° E., 23 lks. dist., mkd. CE 1/16 S9 BT.
ate Received .	3/5/13	A ponderosa pine, 15 ins. diam., bears S. 37° E., 61 lks. dist., mkd. CE 1/16 S9 BT.
ate Filed	3/5/13/	
, Mla	Ellus	
- No O	52-2013R	
O NO.		