

Subdivision of Section 9,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
35.00	Top of ascent, along westerly slope on top of mountain.
39.110	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 9, at intersection with the E. and W. center line.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E C $\frac{1}{4}$ S 9 1991</p>
	<p>from which</p> <p>A larch, 15 ins. diam., bears S. $0\frac{1}{2}^\circ$ W., 61 lks. dist., mkd. C $\frac{1}{4}$ S9 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 85° W., 42 lks. dist., mkd. C $\frac{1}{4}$ S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
	Continue along westerly slope.
44.00	Descend NE. slope.
72.00	Track road, 15 lks. wide, bears irregularly NW. and SE.
78.870	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p> <p>S. $88^\circ 36' 00''$ W., on the E. and W. center line of sec. 9.</p> <p>Ascend E. slope.</p>
4.25	Ridge, bears N. and S.; desc. W. slope.
20.145	<p>Point for the center E $\frac{1}{16}$ sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E $\frac{1}{16}$ C $\frac{1}{16}$ S 9 C 1991</p> <p>from which</p> <p>A fir, 12 ins. diam., bears N. 7° E., 23 lks. dist., mkd. CE $\frac{1}{16}$ S9 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 37° E., 61 lks. dist., mkd. CE $\frac{1}{16}$ S9 BT.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>M. L. G. Moore</i>
File No.	053-2013R