


G-13 LAND CORNER RECORD

5680-2

1. T.S. R.F. File No. G-13 Cor. 111 Mer. 211 State. O.C. N. F.	Dist. UNION
2. Corner Status	
	
Identification	
ENW-9-117	
PIN punched	
Coordinate Position Data	
Zone	
bk No.	
led	
ation	
erif. Monument	
Survey	
Status	
3. Original Description Vol. Page Where Recorded	
4. Description of Corners: STONE 15X9X7 STONE MOUND	
5. Investigation Notes: STONE 16X9X6 LAYING ON TOP. FAINT CHISEL MARKS II AND A POSSIBLY-S- 8 FT NORTH FROM THIS STONE THERE IS A MOUND OF STONE PAINTED RED. WITH A RED AND BLUE STAKE STANDING IN THE CENTER. I TIED YELLOW RIBBON TO THE STONE GO TO UPPER END OF BILLY SMALL RD. WHERE FENCE CROSSES RD. I HAVE TIED YELLOW RIBBON FROM FENCE TO 4 COR.	
6. Signed <u>E.A. Holland</u> Title _____ Date <u>10/7/66</u>	

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-24-87

By G. LANGLITZ, DEPUTY

File No. 425-87R

G-13

464

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon**

CHAINS

A ponderosa pine, 12 ins. diam., bears S. $21\frac{1}{2}^{\circ}$ E.,
91 lks. dist., mkd. T5S R41E S15 BT.

A Douglas fir, 10 ins. diam., bears S. 19° W., 103 lks.
dist., mkd. T5S R41E S16 BT.

A ponderosa pine, 28 ins. diam., bears N. 64° W.,
47 lks. dist., mkd. T5S R41E S9 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the
corner stone alongside the stainless steel post.

N. $0^{\circ} 12' 30''$ W., bet. secs. 9 and 10.

Along W. slope through medium timber and light undergrowth.

Descend NW. slope.

Point for the S 1/16 sec. cor. of secs. 9 and 10.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

S 1/16
S 9 | S 10
1990

from which

A ponderosa pine, 15 ins. diam., bears N. 9° E.,
96 lks. dist., mkd. S 1/16 S10 BT.

A ponderosa pine, 10 ins. diam., bears N. 75° W.,
24 lks. dist., mkd. S 1/16 S9 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.

Dirt road, 20 lks. wide, bears N. 35° E. and S. 35° W.

Stream, 10 lks. wide, course SW.; asc. SE. slope.

21.70

Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins.
in the ground to solid rock, and in a mound of stone, 4 ft. base,
to top, with brass cap mkd.

T 5 S R 41 E
S 9 | $\frac{1}{4}$ S 10
1990

from which

A ponderosa pine, 28 ins. diam., bears N. 7° E.,
25 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

UNION COUNTY SURVEYOR	
Date Received	<u>3/5/13</u>
Date Filed	<u>3/5/13</u>
By	<u>H. G. Glunz</u>
File No.	<u>054-2013R</u>

464

**Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon**

CHAINS

A ponderosa pine, 12 ins. diam., bears S. $21\frac{1}{2}^{\circ}$ E.,
91 lks. dist., mkd. T5S R41E S15 BT.

A Douglas fir, 10 ins. diam., bears S. 19° W., 103 lks.
dist., mkd. T5S R41E S16 BT.

A ponderosa pine, 28 ins. diam., bears N. 64° W.,
47 lks. dist., mkd. T5S R41E S9 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the
corner stone alongside the stainless steel post.

N. $0^{\circ} 12' 30''$ W., bet. secs. 9 and 10.

Along W. slope through medium timber and light undergrowth.

16.20 Descend NW. slope.

19.840 Point for the S 1/16 sec. cor. of secs. 9 and 10.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.

S 1/16
S 9 | S 10
1990

from which

A ponderosa pine, 15 ins. diam., bears N. 9° E.,
96 lks. dist., mkd. S 1/16 S10 BT.

A ponderosa pine, 10 ins. diam., bears N. 75° W.,
24 lks. dist., mkd. S 1/16 S9 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.

21.70 Dirt road, 20 lks. wide, bears N. 35° E. and S. 35° W.

25.25 Stream, 10 lks. wide, course SW.; asc. SE. slope.

39.680 Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate
distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins.
in the ground to solid rock, and in a mound of stone, 4 ft. base,
to top, with brass cap mkd.

T 5 S R 41 E

$\frac{1}{4}$
S 9 | S 10
1990

from which

A ponderosa pine, 28 ins. diam., bears N. 7° E.,
25 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By RLQ/MR

File No. 054-2013R