

Subdivision of Section 9,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	S. 88° 59' 00" W., on the E. and W. center line of the SE¼ of sec. 9.
	Descend W. slope, through medium timber and light undergrowth.
1.20	Dirt road, 20 lks. wide, bears NE. and SW.
20.030	The SE 1/16 sec. cor. of sec. 9.
	Descend W. slope, along N. edge of logged area.
23.50	Stream, 15 lks. wide, course S. 30° W.; asc. SE. slope.
32.00	Slope changes to S.
40.065	The center S 1/16 sec. cor. of sec. 9.
<p>Subdivision of Section 10, T. 5 S., R. 41 E., Willamette Meridian, Oregon</p>	
	From the ¼ sec. cor. of secs. 10 and 15.
	N. 0° 23' 30" W., on the N. and S. center line of sec. 10.
	Along W. slope.
	Descend NW. slope.
11.70	Bottom of descent; asc. gradually over SW. slope.
22.65	Graveled road, 25 lks. wide, bears N. 30° W. and S. 30° E.
36.75	Ravine, drains SW.
39.580	Point for the center ¼ sec. cor. of sec. 10, at intersection with the E. and W. center line.
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock, and in a collar of stone, with brass cap mkd.
	<p>T 5 S R 41 E C¼ S 10 1991</p>
	from which
	A fir, 15 ins. diam., bears S. 83° E., 11½ lks. dist., mkd. C¼ S10 BT.
	A ponderosa pine, 20 ins. diam., bears N. 16½° W., 40 lks. dist., mkd. C¼ S10 BT.
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
	Continue to asc. SW. slope, through medium timber and light undergrowth.

UNION COUNTY SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By MLG

File No. 055-2013R

