

501

Subdivision of Section 10,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
59.485	<p>Point for the center N 1/16 sec. cor. of sec. 10.</p> <p>Set a brass tablet, 3¼ ins. diam., 3½ in. stem, in a drill hole on the SW. portion of a boulder, 12 ft. x 9 ft. x 8 ft., with top mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad   \quad \text{S } 10 \\ \text{C} \\ 1991 \end{array}</math> </div> <p>from which</p> <p>A Douglas fir, 16 ins. diam., bears N. 35° E., 11 lks. dist., mkd. CN 1/16 S10 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 7° E., 14 lks. dist., mkd. CN 1/16 S10 BT.</p> <p>Continue along W. slope, through logged area.</p>
79.390	<p>The ¼ sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the ¼ sec. cor. of secs. 10 and 11.</p> <p>S. 89° 28' 30" W., on the E. and W. center line of sec. 10.</p> <p>Descend W. slope, through logged area.</p>
16.05	<p>Dirt road, 15 lks. wide, bears N. and S.</p>
19.805	<p>Point for the center E 1/16 sec. cor. of sec. 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} \text{E } 1/16 \\ \text{C} \quad \frac{\quad}{\quad} \quad \text{C} \\ \text{S } 10 \\ 1991 \end{array}</math> </div> <p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears S. 60° E., 6 lks. dist., mkd. CE 1/16 S10 BT.</p> <p>A larch, 16 ins. diam., bears S. 19° W., 57 lks. dist., mkd. CE 1/16 S10 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue to descend W. slope changing to sw. slope.</p>
39.610	<p>The center ¼ sec. cor. of sec. 10.</p>
50.60	<p>Graveled road, 20 lks. wide, bears N. 65° W. and SE., in a curve.</p>
64.35	<p>Dirt road, 20 lks. wide, bears NW. and SE.</p>

UNION COUNTY  
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

File No.

56-2013R