

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

T 5 S R 41 E
S 11
 $\frac{1}{4}$ ———
S 14
1990

**UNION COUNTY
SURVEYOR**

Date Received 3/5/13

Date Filed 3/5/13

By R. J. G. Miller

File No. 057-2013R

from which new bearing trees

A larch, 9 ins. diam., bears N. 77° E., 39 lks. dist.,
mkd. $\frac{1}{4}$ S11 BT.

A lodgepole pine, 14 ins. diam., bears S. 58° E.,
41 lks. dist., mkd. $\frac{1}{4}$ S14 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the
corner stone alongside the stainless steel post.

S. 88° 58' 00" W., bet. secs. 11 and 14.

Descend broken W. slope.

39.600

The cor. of secs. 10, 11, 14, and 15.

N. 0° 38' 30" W., bet. secs. 10 and 11.

Ascend SW. slope through medium timber and light undergrowth.

3.40

Spur, slopes W.; over broken W. slope.

23.80

Rocky spur, slopes SW.

39.950

The $\frac{1}{4}$ sec. cor. of secs. 10 and 11, determined at the center of
the remains of a mound of stone crushed by a bulldozer, with a
broken piece of the original stone, 8 x 6 x 4 ins. (record, 15 x
11 x 11 ins.), alongside, mkd. $\frac{1}{4}$.

At the corner point

Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins.
in the ground, and in a collar of stone, with brass cap mkd.

T 5 S R 41 E
S 10 | S 11
 $\frac{1}{4}$ ———
1990

from which new bearing trees

A fir, 15 ins. diam., bears N. 78° E., 36 lks. dist.,
mkd. $\frac{1}{4}$ S11 BT.

A fir, 12 ins. diam., bears S. 54 $\frac{1}{4}$ ° W., 48 lks. dist.,
mkd. $\frac{1}{4}$ S10 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the
remains of the corner stone alongside the stainless steel post.

N. 0° 08' 00" W., beginning new measurement.