

Subdivision of Section 4,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	<p>Ascend E. slope.</p> <p>79.285 The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>N. 2° 37' 30" W., on the N. and S. center line of the SE 1/4 of sec. 4.</p> <p>Descend over broken NW. slope, through logged area.</p> <p>4.40 Track road, 20 lks. wide, bears NE. and SW.</p> <p>7.40 Creek, 5 lks. wide, course N. 50° W.</p> <p>8.50 Track road, 15 lks. wide, bears NW. and SE., over broken W. slope.</p> <p>28.00 Ravine, drains S. 60° W.; asc. S. slope.</p>
<p>UNION COUNTY SURVEYOR</p>	<p>The center E 1/16 sec. cor. of sec. 4.</p> <hr/> <p style="text-align: center;">Subdivision of Section 9, T. 5 S., R. 41 E., Willamette Meridian, Oregon</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0° 49' 00" W., on the N. and S. center line of sec. 9.</p> <p>Along W. edge of logged area.</p> <p>Stream, 10 lks. wide, course SW.; asc. SE. slope changing to S. slope, along W. edge of logged area.</p>
<p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/13</u></p> <p>By <u>ML Salms</u></p> <p>File No. <u>058-2013R</u></p>	<p>19.555 Point for the center S 1/16 sec. cor. of sec. 9.</p> <p>Set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 1/16 S 9</p> <p style="margin: 0;">C</p> <p style="margin: 0;">C</p> <p>1991</p> </div> <p>from which</p> <p style="margin-left: 40px;">A ponderosa pine, 22 ins. diam., bears N. 26° E., 14 lks. dist., mkd. CS 1/16 S9 BT.</p> <p style="margin-left: 40px;">A ponderosa pine, 24 ins. diam., bears S. 70° W., 37 lks. dist., mkd. CS 1/16 S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
<p>3.00</p> <p>22.40</p>	<p>Ascend S. slope, through medium timber and light undergrowth.</p> <p>Graveled road, 25 lks. wide, bears E. and W.</p>