

499

Subdivision of Section 9,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
22.10	Graveled road, 25 lks. wide, bears N. and S., in a saddle; asc. E. slope.
38.50	Top of ascent; desc. W. slope.
40.290	The center $\frac{1}{4}$ sec. cor. of sec. 9.
	Descend over broken W. slope, through medium timber and light undergrowth.
80.05	Graveled road, 25 lks. wide, bears NE. and SW., in a curve.
81.300	The $\frac{1}{4}$ sec. cor. of secs. 8 and 9.
	<hr/> From the E $\frac{1}{16}$ sec. cor. of secs. 9 and 16. N. $0^{\circ} 30' 30''$ W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 9. Ascend SE. slope, along E. edge of logged area.
0.170	Barbed wire fence, extends E. and W.
4.00	Saddle, bears NE. and SW.; continue along W. slope at E. edge of logged area.
19.700	Point for the SE $\frac{1}{16}$ sec. cor. of sec. 9, at intersection with the E. and W. center line of the SE $\frac{1}{4}$. Set a stainless steel post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd. <div style="text-align: center;">SE $\frac{1}{16}$ S 9 1991</div> from which A ponderosa pine, 14 ins. diam., bears N. 28° E., 7 $\frac{1}{2}$ lks. dist., mkd. X at breast height and BT at the base. A ponderosa pine, 15 ins. diam., bears S. 9° E., 4 lks. dist., mkd. SE $\frac{1}{16}$ S9 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.
20.20	Spur, slopes W.
22.00	Stream, 10 lks. wide, course N. 80° W. changing to SW.; asc. SW. slope.
39.400	The center E $\frac{1}{16}$ sec. cor. of sec. 9.
	<hr/> From the S $\frac{1}{16}$ sec. cor. of secs. 9 and 10.

UNION COUNTY
SURVEYOR

Date Received 3/5/13Date Filed 3/5/13By WLGFile No. 059-2013R