

464

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A ponderosa pine, 12 ins. diam., bears S. 21½° E., 91 lks. dist., mkd. T5S R41E S15 BT.</p> <p>A Douglas fir, 10 ins. diam., bears S. 19° W., 103 lks. dist., mkd. T5S R41E S16 BT.</p> <p>A ponderosa pine, 28 ins. diam., bears N. 64° W., 47 lks. dist., mkd. T5S R41E S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p> <hr/> <p>N. 0° 12' 30" W., bet. secs. 9 and 10.</p> <p>Along W. slope through medium timber and light undergrowth.</p>
16.20	Descend NW. slope.
19.840	<p>Point for the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 9 S 10 1990</p> <p>from which</p> <p>A ponderosa pine, 15 ins. diam., bears N. 9° E., 96 lks. dist., mkd. S 1/16 S10 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 75° W., 24 lks. dist., mkd. S 1/16 S9 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
21.70	Dirt road, 20 lks. wide, bears N. 35° E. and S. 35° W.
25.25	Stream, 10 lks. wide, course SW.; asc. SE. slope.
39.680	<p>Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 9 S 10 1990</p> <p>from which</p> <p>A ponderosa pine, 28 ins. diam., bears N. 7° E., 25 lks. dist., mkd. ¼ S10 BT.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>N. L. Gilman</i>
File No.	060-2013R