

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

A Douglas fir, 20 ins. diam., bears N. 12° E., 52 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, N. 13° E.)

A Douglas fir, 24 ins. diam., bears S. 62° E., 244 lks. dist., with scribe marks $\frac{1}{5}$ visible on partially healed blaze. (Record, S. 60° E.)

The corner is located 0.05 chs. S. of a barbed wire fence, extending E. and W.

S. 87° 33' 30" W., beginning new measurement.

Descend along fence line at N. edge of logged area and along creek, draining W.

40.410

Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T	5	S	R	41	E
S	8		S	9	
S	17		S	16	
1990					

from which

A fir, 8 ins. diam., bears N. 38° E., 53 lks. dist., mkd. T5S R41E S9 BT.

A fir, 22 ins. diam., bears S. 39° E., 63 lks. dist., mkd. T5S R41E S16 BT.

A fir, 25 ins. diam., bears S. 55° W., 38 lks. dist., mkd. T5S R41E S17 BT.

A ponderosa pine, 25 ins. diam., bears N. 56½° W., 132 lks. dist., mkd. T5S R41E S8 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of secs. 16, 17, 20, and 21, bears S. 0° 53' 30" E., 79.620 chs. dist., monumented with the original unmarked slate stone, 10 x 8 x 8 ins., loosely set at the center of a stone mound, alongside find an iron pipe, 2 ins. diam., firmly set, projecting 5 ins. above ground, with metal washer mkd. CX 15 1973.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

RLG

File No.

065-2013R