

J-11 T55 R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON POST 28" Long Set 22" IN ground
With 5' Steel Fence Post Along side

T55 R41E	BRASS
1/4 S 9	CAP
1/4 S 16	MKD
1971	

ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A Fir 15" BRS N 13° E 52 LNS MKD 1/4 S 9 BT

A Fir 16" BRS S 60° E 244 LNS MKD 1/4 S 16 BT

Work Done By SALBRIGHT Title CADASTRAL SURVEYOR Date 9/28/71 State Registration No. 225828 BLM
 Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No. T. R. M. Tract or Surv. No. Cor. _____

UNION COUNTY SURVEYOR	
Date Received	_____
Date Filed	<u>12-24-87</u>
By	<u>S. LANGLITZ, DEPUTY</u>
File No.	<u>426-87R</u>

5-11

474

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS											
	From the cor. of secs. 9, 10, 15, and 16.										
	S. 89° 23' 30" W., bet. secs. 9 and 16.										
	Descend W. slope through medium timber and light undergrowth.										
1.50	Barbed wire fence, extends irregularly N. and S.										
7.30	Dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.; desc. SW. slope.										
16.50	Ravine, drains S.; asc. SE. slope.										
19.50	Wire fence, bears N. and S.										
19.920	Point for the E 1/16 sec. cor. of secs. 9 and 16.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border: none;">E 1/16</td> <td style="border: none; text-align: center;"> <table style="border-collapse: collapse;"> <tr> <td style="border: none;">S 9</td> <td style="border: none; border-bottom: 1px solid black;"> </td> </tr> <tr> <td style="border: none;">S 16</td> <td style="border: none;"> </td> </tr> <tr> <td style="border: none;">1990</td> <td style="border: none;"> </td> </tr> </table> </td> </tr> </table>	E 1/16	<table style="border-collapse: collapse;"> <tr> <td style="border: none;">S 9</td> <td style="border: none; border-bottom: 1px solid black;"> </td> </tr> <tr> <td style="border: none;">S 16</td> <td style="border: none;"> </td> </tr> <tr> <td style="border: none;">1990</td> <td style="border: none;"> </td> </tr> </table>	S 9		S 16		1990			
E 1/16	<table style="border-collapse: collapse;"> <tr> <td style="border: none;">S 9</td> <td style="border: none; border-bottom: 1px solid black;"> </td> </tr> <tr> <td style="border: none;">S 16</td> <td style="border: none;"> </td> </tr> <tr> <td style="border: none;">1990</td> <td style="border: none;"> </td> </tr> </table>	S 9		S 16		1990					
S 9											
S 16											
1990											
	from which										
	A ponderosa pine, 24 ins. diam., bears N. 75° E., 105 lks. dist., mkd. E 1/16 S9 BT.										
	A Douglas fir, 25 ins. diam., bears S. 29° W., 39 lks. dist., mkd. E 1/16 S16 BT.										
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.										
	From this point, the corner of wire fences, extending E., W., and S., bears N. 69° E., 0.470 chs. dist.										
21.50	Spur, slopes S.; desc. SW. slope.										
39.840	The ¼ sec. cor. of secs. 9 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.										
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border: none;">T 5 S R 41 E</td> <td style="border: none;"> </td> </tr> <tr> <td style="border: none;">S 9</td> <td style="border: none; border-bottom: 1px solid black;"> </td> </tr> <tr> <td style="border: none;">¼</td> <td style="border: none;"> </td> </tr> <tr> <td style="border: none;">S 16</td> <td style="border: none;"> </td> </tr> <tr> <td style="border: none;">1971</td> <td style="border: none;"> </td> </tr> </table>	T 5 S R 41 E		S 9		¼		S 16		1971	
T 5 S R 41 E											
S 9											
¼											
S 16											
1971											
	from which the remains of an original bearing tree										
	A sawed pine stump, 28 ins. diam., bears N. 42° E., 28 lks. dist., no marks.										
	and bearing trees mkd. by Albright										

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>N. J. G. Miller</i>
File No.	066-2013R

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

A Douglas fir, 20 ins. diam., bears N. 12° E., 52 lks. dist., with fragmentary scribe marks visible on partially healed blaze. (Record, N. 13° E.)

A Douglas fir, 24 ins. diam., bears S. 62° E., 244 lks. dist., with scribe marks $\frac{1}{4}$ S visible on partially healed blaze. (Record, S. 60° E.)

The corner is located 0.05 chs. S. of a barbed wire fence, extending E. and W.

S. 87° 33' 30" W., beginning new measurement.

Descend along fence line at N. edge of logged area and along creek, draining W.

40.410

Point for the cor. of secs. 8, 9, 16, and 17, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 5 S	R 41 E
S 8	S 9
S 17	S 16
1990	

from which

A fir, 8 ins. diam., bears N. 38° E., 53 lks. dist., mkd. T5S R41E S9 BT.

A fir, 22 ins. diam., bears S. 39° E., 63 lks. dist., mkd. T5S R41E S16 BT.

A fir, 25 ins. diam., bears S. 55° W., 38 lks. dist., mkd. T5S R41E S17 BT.

A ponderosa pine, 25 ins. diam., bears N. 56½° W., 132 lks. dist., mkd. T5S R41E S8 BT.

Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

From this point, the cor. of secs. 16, 17, 20, and 21, bears S. 0° 53' 30" E., 79.620 chs. dist., monumented with the original unmarked slate stone, 10 x 8 x 8 ins., loosely set at the center of a stone mound, alongside find an iron pipe, 2 ins. diam., firmly set, projecting 5 ins. above ground, with metal washer mkd. CX 15 1973.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By



File No.

066-2013R

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S R 41 E

¼ $\frac{S 21}{S 28}$

1971

from which new bearing trees

A white fir, 14 ins. diam., bears N. 42° E., 57½ lks. dist., mkd. ¼ S21 ET.

A white fir, 13 ins. diam., bears S. 34½° E., 38 lks. dist., mkd. ¼ S28 ET.

Deposit corner stone and set 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 9 and 16, determined at record bearing and distance from the original bearing trees:

A ponderosa pine, 28 ins. diam., bears N. 42° E., 28 lks. dist., with axe marks visible on opened and burned blaze.

A western larch snag, 18 ins. diam., bears S. 61° E., 23 lks. dist., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 41 E

¼ $\frac{S 9}{S 16}$

1971

from which new bearing trees

A fir, 15 ins. diam., bears N. 13° E., 52 lks. dist., mkd. ¼ S9 ET.

A fir, 16 ins. diam., bears S. 60° E., 244 lks. dist., mkd. ¼ S16 ET.

Set 5 ft. steel fence post alongside iron post.

The ¼ sec. cor. of secs. 8 and 9, determined at record bearing and distance from the only remaining original bearing tree:

A root hole, bears N. 45° E., 24 lks. dist., with a down and decayed pine alongside, size indeterminate, with scribe marks ¼ S visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

M. J. Galun

File No.

010-2013R