

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS											
	From the cor. of secs. 9, 10, 15, and 16.										
	S. 89° 23' 30" W., bet. secs. 9 and 16.										
	Descend W. slope through medium timber and light undergrowth.										
1.50	Barbed wire fence, extends irregularly N. and S.										
7.30	Dirt road, 20 lks. wide, bears N. 50° E. and S. 50° W.; desc. SW. slope.										
16.50	Ravine, drains S.; asc. SE. slope.										
19.50	Wire fence, bears N. and S.										
19.920	Point for the E 1/16 sec. cor. of secs. 9 and 16.										
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.										
	<div style="text-align: center;"> <table border="0"> <tr><td></td><td style="text-align: center;">S 9</td></tr> <tr><td style="text-align: center;">E 1/16</td><td style="text-align: center;">—</td></tr> <tr><td></td><td style="text-align: center;">S 16</td></tr> <tr><td></td><td style="text-align: center;">1990</td></tr> </table> </div>		S 9	E 1/16	—		S 16		1990		
	S 9										
E 1/16	—										
	S 16										
	1990										
	from which										
	A ponderosa pine, 24 ins. diam., bears N. 75° E., 105 lks. dist., mkd. E 1/16 S9 BT.										
	A Douglas fir, 25 ins. diam., bears S. 29° W., 39 lks. dist., mkd. E 1/16 S16 BT.										
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.										
	From this point, the corner of wire fences, extending E., W., and S., bears N. 69° E., 0.470 chs. dist.										
21.50	Spur, slopes S.; desc. SW. slope.										
39.840	The ¼ sec. cor. of secs. 9 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.										
	<div style="text-align: center;"> <table border="0"> <tr><td></td><td style="text-align: center;">T 5 S R 41 E</td></tr> <tr><td></td><td style="text-align: center;">S 9</td></tr> <tr><td style="text-align: center;">¼</td><td style="text-align: center;">—</td></tr> <tr><td></td><td style="text-align: center;">S 16</td></tr> <tr><td></td><td style="text-align: center;">1971</td></tr> </table> </div>		T 5 S R 41 E		S 9	¼	—		S 16		1971
	T 5 S R 41 E										
	S 9										
¼	—										
	S 16										
	1971										
	from which the remains of an original bearing tree										
	A sawed pine stump, 28 ins. diam., bears N. 42° E., 28 lks. dist., no marks.										
	and bearing trees mkd. by Albright										

<b>UNION COUNTY SURVEYOR</b>	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>Albright</i>
File No.	C67-2013R