


9-13 LAND CORNER RECORD

5680-2

1. T. S.S. R. 4/E No. J-13 Cor. Sec 11 Mer Will State Ill N. F. W W Dist. UNION

2. Corner Status



7. Photo Identification

Photo No. EKW-9-118
Ident. By: PIX Punched

8. Plane Coordinate Position Data

State _____ Zone _____
X _____
Y _____
Estab. By _____
Field Book No. _____
Where Filed _____

9. Evaluation

Authentic _____
Needs Verif. _____ Monument _____
Re-estab. _____ Survey _____
Land Status _____

3. Original Description _____ Vol. _____ Page _____ Where Recorded _____

4. Description of Corners: STONE 18 X 16 X 8

5. Investigation Notes: STONE MOUND FROM WHICH A 22" PP WITH SCRIBING - S-BEAR'S N45°30'W 23.5' dist. A 22" PP BEAR'S - S13°00'E 48' dist. DOES NOT FIT ORIGINAL NOTES

I HUNG YELLOW RIBBON AT SEC. COR. GO UP MERRY GO ROUND RD. FROM CATH. CT. TO THE FOURTH GATE AND FOLLOW FENCE EAST.

6. Signed E.A. Hildner Title _____ Date 10/6/66

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-24-87

By G. LANGLITZ, DEPUTY

File No. 427-87R

9-13

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

A fir, 22 ins. diam., bears N. 40° E., 14 lks. dist.,
with open blaze, no marks visible.

A fir, 16 ins. diam., bears S. 30° E., 31 lks. dist.,
with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap mkd.

| | |
|-------|--------|
| T 5 S | R 41 E |
| S 10 | |
| ¼ | |
| S 15 | |
| 1990 | |

from which new bearing trees

A larch, 10 ins. diam., bears N. 0½° E., 57½ lks. dist.,
mkd. ¼ S10 BT.

A ponderosa pine, 16 ins. diam., bears S. 13° W.,
108 lks. dist., mkd. ¼ S15 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the
remains of the original stone alongside the stainless steel post.

S. 89° 21' 30" W., beginning new measurement.

Descend W. slope, through medium timber and light undergrowth.

39.00 Broad ridge, bears N. and S.

39.990 The cor. of secs. 9, 10, 15, and 16, monumented with the original
slate stone, 18 x 15 x 7 ins. (record, 18 x 16 x 8 ins.), loosely
set at the center of a stone mound, 4 ft. diam., with 3 grooves on
E. face, from which a bearing tree not of record:

A ponderosa pine, 27 ins. diam., bears N. 41° W., 37 lks.
dist., with curved scribe mark visible on open blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in
the ground to solid rock, and in a mound of stone, 5 ft. base, to
top, with brass cap mkd.

| | |
|-------|--------|
| T 5 S | R 41 E |
| S 9 | S 10 |
| S 16 | S 15 |
| 1990 | |

from which new bearing trees

A ponderosa pine, 15 ins. diam., bears N. 41° E.,
45 lks. dist., mkd. T5S R41E S10 BT.

**UNION COUNTY
SURVEYOR**

Date Received 3/5/13

Date Filed 3/5/13

By DL Galt

File No. 068-2013R