

10. Monument:

Accessories

Set By _____
Date _____
Agency _____

Remarks:

PROPERTY CORNER INVESTIGATION


J-15

LOCATION

T. 55 R. 41E

Mer. Wm State Oregon

Forest W-W Dist. Union



LEGEND

- Corner searched-no evidence
- Corner or accessory found
- Corner marked by perm. mon.

DESCRIPTION OF FOUND CORNER

MATERIAL: Stone SIZE: 19x13x3

HEIGHT ABOVE GROUND: 14" CONDITION: good

MARKINGS: _____

DESCRIPTION OF FOUND ACCESSORIES

BT's probably burned + rotten

No definite evidence

NOTE: Indicate full investigative details on back of form.

PHOTO IDENTIFICATION

Symbol & date ENW 7/64 Line or Roll 9 Exposure 117

How Identified Pin Point Where filed Union R.D.

DATE: 6/21/64

RECOVERED BY: Jillenciste Thomas

TITLE: Forester

Form R6-5680-180 (4/61)

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-24-87

By G. LANGLITZ, DEPUTY

File No. 428-87R

J-15

462

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS							
	<p>Deposit a white "DEEP-1" magnetic marker at the base and set a 6 ft. steel fence post alongside the stainless steel post.</p> <p>The corner is located 0.450 chs. S. of a barbed wire fence extending E. and W.</p>						
67.50	Ridge, slopes S. 30° E.; desc. SW. slope.						
79.600	The cor. of secs. 15, 16, 21, and 22.						
	<hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p>						
	N. 89° 58' 30" W., bet. secs. 10 and 15.						
	Descend SW. slope, through medium timber and light undergrowth.						
16.90	Dirt road, 15 lks. wide, bears N. and S.						
19.910	Point for the E 1/16 sec. cor. of secs. 10 and 15.						
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>						
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td></td> <td style="text-align: center;">S 10</td> </tr> <tr> <td style="text-align: center;">E 1/16</td> <td style="border-top: 1px solid black; border-left: 1px solid black; border-right: 1px solid black;">S 15</td> </tr> <tr> <td></td> <td style="text-align: center;">1990</td> </tr> </table>		S 10	E 1/16	S 15		1990
	S 10						
E 1/16	S 15						
	1990						
	from which						
Date Received	<p>3/5/13</p> <p>A ponderosa pine, 12 ins. diam., bears S. 21° E., 37 lks. dist., mkd. E 1/16 S15 BT.</p>						
Date Filed	<p>3/5/13</p> <p>A ponderosa pine, 14 ins. diam., bears N. 87° W., 30 lks. dist., mkd. E 1/16 S10 BT.</p>						
By	<p><i>W.L. Gilman</i></p>						
File No.	<p>069-2013R</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>						
	Continue to desc. SW. slope.						
30.30	Graveled road, 20 lks. wide, bears N. 30° W. and S. 30° E.; desc. W. slope through logged area.						
39.820	<p>The ¼ sec. cor. of secs. 10 and 15, monumented with the remains of the unmarked original stone, 11 x 6 x 3 ins. (record, 19 x 13 x 3 ins.), firmly set and broken at the center of the remains of a stone mound crushed by a bulldozer, from which the remains of the original bearing trees:</p> <p style="padding-left: 40px;">A burned pine snag, 20 ins. diam., bears N. 60° E., 15 lks. dist., no marks. (Record, 23 lks.)</p> <p style="padding-left: 40px;">The burned remains of a stump, size and species indeterminate, in a root hole, bears S. 50° W., 23 lks. dist., no marks. (Record, 15 lks.)</p> <p>and bearing trees not of record</p>						

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

W.L. Gilman

File No.

069-2013R

463

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

A fir, 22 ins. diam., bears N. 40° E., 14 lks. dist.,
with open blaze, no marks visible.

A fir, 16 ins. diam., bears S. 30° E., 31 lks. dist.,
with healed blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap mkd.

T 5 S R 41 E
S 10
¼
S 15
1990

from which new bearing trees

A larch, 10 ins. diam., bears N. 0½° E., 57½ lks. dist.,
mkd. ¼ S10 BT.

A ponderosa pine, 16 ins. diam., bears S. 13° W.,
108 lks. dist., mkd. ¼ S15 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the
remains of the original stone alongside the stainless steel post.

S. 89° 21' 30" W., beginning new measurement.

Descend W. slope, through medium timber and light undergrowth.

39.00

Broad ridge, bears N. and S.

39.990

The cor. of secs. 9, 10, 15, and 16, monumented with the original
slate stone, 18 x 15 x 7 ins. (record, 18 x 16 x 8 ins.), loosely
set at the center of a stone mound, 4 ft. diam., with 3 grooves on
E. face, from which a bearing tree not of record:

A ponderosa pine, 27 ins. diam., bears N. 41° W., 37 lks.
dist., with curved scribe mark visible on open blaze.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 6 ins. in
the ground to solid rock, and in a mound of stone, 5 ft. base, to
top, with brass cap mkd.

T 5 S R 41 E
S 9 | S 10
S 16 | S 15
1990

from which new bearing trees

A ponderosa pine, 15 ins. diam., bears N. 41° E.,
45 lks. dist., mkd. T5S R41E S10 BT.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

Art G. Allen

File No.

069-2013R