

449

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

N 1/16
S 15 | S 14
1991

from which

~~A larch, 13 ins. diam., bears S. 11½° E., 62 lks. dist.,
mkd. N 1/16 S14 BT.~~

~~A Douglas fir, 20 ins. diam., bears N. 34° W., 50 lks.
dist., mkd. N 1/16 S15 BT.~~

~~Deposit a white "DEEP-1" magnetic marker at the base of the
stainless steel post.~~

67.00 Ascend SW. slope.

81.920 The cor. of secs. 10, 11, 14, and 15, monumented with the original
slate stone, 12 x 10 x 4 ins. (record, 16 x 12 x 6 ins.), firmly
set 3 ins. in the ground at the edge of an old stone mound, mkd.
with 3 grooves on the E. face and 2 grooves on the S. face.

At the corner point

Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, and in a collar of stone, with brass cap mkd.

T 5 S R 41 E
S 10 | S 11
S 15 | S 14
1990

from which new bearing trees

A ponderosa pine, 16 ins. diam., bears N. 72° E.,
69 lks. dist., mkd. T5S R41E S11 BT.

A ponderosa pine, 20 ins. diam., bears S. 21° E.,
25 lks. dist., mkd. T5S R41E S14 BT.

A larch, 13 ins. diam., bears S. 54° W., 91 lks. dist.,
mkd. T5S R41E S15 BT.

A ponderosa pine, 9 ins. diam., bears N. 9½° W.,
126 lks. dist., mkd. T5S R41E S10 BT.

Deposit a white "DEEP-1" magnetic marker at the base and the
corner stone alongside the stainless steel post.

~~From the ¼ sec. cor. of secs. 11 and 14, monumented with the
original slate stone, 17 x 11 x 3 ins. (record, 17 x 11 x 8 ins.),
firmly set, projecting 6 ins. above ground, with illegible chisel
marks on the S. face.~~

~~At the corner point~~

~~Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins.
in the ground, with brass cap mkd.~~

UNION COUNTY
SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By *R.L.G. [Signature]*

File No. 071-203R