

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS													
19.730	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td></td><td style="text-align: center;">S 14</td></tr> <tr><td style="text-align: center;">W 1/16</td><td style="text-align: center;">—</td></tr> <tr><td></td><td style="text-align: center;">S 23</td></tr> <tr><td></td><td style="text-align: center;">1991</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 67° W., 71 lks. dist., mkd. W 1/16 S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 63½° W., 85 lks. dist., mkd. W 1/16 S14 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>		S 14	W 1/16	—		S 23		1991				
	S 14												
W 1/16	—												
	S 23												
	1991												
39.460	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> <p>N. 0° 45' 00" W., bet. secs. 14 and 15.</p> <p>Ascend along E. edge of rocky ridge.</p>												
7.50	<p>Slope changes to W. slope.</p>												
40.960	<p>Point for the ¼ sec. cor. of secs. 14 and 15 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="3" style="text-align: center;">T 5 S R 41 E</td></tr> <tr><td></td><td style="text-align: center;">¼</td><td></td></tr> <tr><td style="text-align: center;">S 15</td><td style="text-align: center;"> </td><td style="text-align: center;">S 14</td></tr> <tr><td></td><td></td><td style="text-align: center;">1991</td></tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 25° E., 7 lks. dist., mkd. ¼ S14 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 79° W., 179 lks. dist., mkd. ¼ S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue along W. slope through logged area.</p>	T 5 S R 41 E				¼		S 15		S 14			1991
T 5 S R 41 E													
	¼												
S 15		S 14											
		1991											
56.60	<p>Graveled road, 25 lks. wide, bears N. 10° W. and S. 30° E.</p>												
61.440	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>												

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>Richard B. Palmer</i>
File No.	073-2013R

449

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">N 1/16 S 15 S 14 1991</p> <p>from which</p> <p style="padding-left: 40px;">A larch, 13 ins. diam., bears S. 11½° E., 62 lks. dist., mkd. N 1/16 S14 BT.</p> <p style="padding-left: 40px;">A Douglas fir, 20 ins. diam., bears N. 34° W., 50 lks. dist., mkd. N 1/16 S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
67.00	Ascend SW. slope.
81.920	<p>The cor. of secs. 10, 11, 14, and 15, monumented with the original slate stone, 12 x 10 x 4 ins. (record, 16 x 12 x 6 ins.), firmly set 3 ins. in the ground at the edge of an old stone mound, mkd. with 3 grooves on the E. face and 2 grooves on the S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 10 S 11 S 15 S 14 1990</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 72° E., 69 lks. dist., mkd. T5S R41E S11 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 21° E., 25 lks. dist., mkd. T5S R41E S14 BT.</p> <p style="padding-left: 40px;">A larch, 13 ins. diam., bears S. 54° W., 91 lks. dist., mkd. T5S R41E S15 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 9½° W., 126 lks. dist., mkd. T5S R41E S10 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>
	<p>From the ¼ sec. cor. of secs. 11 and 14, monumented with the original slate stone, 17 x 11 x 3 ins. (record, 17 x 11 x 8 ins.), firmly set, projecting 6 ins. above ground, with illegible chisel marks on the S. face.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>R. L. B. Allen</i>
File No.	073-2013R