

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

INDEX No. L-21

History of original corner establishment:

This corner was originally established by Henry M. Thatcher under GLO Contract No. 320, dated April 1, 1879. The Surveyor General Record states:

DIAGRAM
T5S R41E
1/4
S14|S13
1991
(BLM Brass Cap)

Set stone 12x10x8 for 1/4 Sec. Cor. Raised stone mound at Cor.

In 1990 the Bureau of Land Management (BLM) conducted a dependent resurvey in T.5S., R.41E., W.M., under Group Nos. 1000 and 1484. This survey was executed by Philip G. Griffin, Cadastral Surveyor and commenced July 9, 1990 and was completed April 13, 1992. The following is the BLM's record for this corner:

The 1/4 sec. cor. of secs. 13 and 14, monumented with the original unmarked basalt stone, 14x12x8 ins. (record, 12x10x8 ins.), firmly set, projecting 6 ins. above ground, with remains of old stone mound alongside. At the corner point set a stainless steel post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd. SEE DIAGRAM, from which new bearing trees: a pine, 9 ins. diam., bears N78 1/2°E, 24 lks. dist., mkd. 1/4 S13 BT. A pine, 15 ins. diam., bears N89°W, 11 lks. dist., mkd. 1/4 S14 BT. Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post. Raise a mound of stone, 4 ft. base, 1 1/2 ft. high, W. of the corner.

Description of Corner Evidence Found:

Found a 2 1/2" dia. stainless steel post with brass cap marked as shown in diagram, in a large mound of stone, 3 ft. at base, 6 inches high. Monument is solid and in good condition.

A Ponderosa Pine, 9" dia., with blaze pitched over, bears N78 1/2°E, 15.84 ft. (Established by BLM)

A Ponderosa Pine, 15" dia., with blaze pitched over, bears N89°W, 7.26 ft. (Established by BLM)

A large mound of stone, 4 ft. base, 1 1/2 ft. high, is west of the corner.

Description of monument and accessories I established to perpetuate the original location of this corner:

No work is needed on the monument.
From Which:

Ponderosa Pine, 7" dia., bears S20°E, 16.8 ft., scribed: X BT
Ponderosa Pine, 11" dia., bears S20°W, 32.3 ft., scribed: 1/4 S14 BT

Measurements to BT's taken with magnetic compass, with the declination set at 20°E and chain. Nailed Bearing Tree (54-3) signs above blaze and Land Survey Monument (54-9) signs on back of each tree as required. Painted a 6" red band above Bearing Trees signs. Set 1/2" brass disc at base of blaze stamped: "L. Miller PLS 2513".



Revised 12-26-96

This corner maintenance was performed by:
Linda Lee Miller, PLS 2513
May 21, 1995

UNION COUNTY CLERK
Date Received <u>2-2-96</u>
Date Filed <u>2-5-96</u>
By <u>R. Robinson, Deputy</u>
PLS No. <u>017-1996R</u>

Office of _____ County of _____
State of _____ I hereby certify that the within instrument was
filed in this office for record on the _____ day of _____ 19____
by _____ (COUNTY OFFICIAL) _____ (DEPUTY)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A ponderosa pine, 17 ins. diam., bears S. 51° W., 82 lks. dist., mkd. W 1/16 S24 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
67.30	<p>North Fork of Catherine Creek, 50 lks. wide, course S. 40° W.; continue over creek bottom land.</p>
70.00	<p>Graveled road, 25 lks. wide, bears N. 80° E. and S. 80° W.; asc. SE. slope.</p>
76.600	<p>The cor. of secs. 13, 14, 23, and 24.</p> <hr/> <p>N. 0° 43' 30" W., bet. secs. 13 and 14.</p> <p>Ascend steep S. slope, through medium timber and light undergrowth.</p>
9.00	<p>Across nearly level bench, changing to SW. slope.</p>
39.660	<p>The ¼ sec. cor. of secs. 13 and 14, monumented with the original unmarked basalt stone, 14 x 12 x 8 ins. (record, 12 x 10 x 8 ins.), firmly set, projecting 6 ins. above ground, with remains of old stone mound alongside.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 14 S 13 1991</p> <p>from which new bearing trees</p> <p>A pine, 9 ins. diam., bears N. 78½° E., 24 lks. dist., mkd. ¼ S13 BT.</p> <p>A pine, 15 ins. diam., bears N. 89° W., 11 lks. dist., mkd. ¼ S14 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p> <p>Raise a mound of stone, 4 ft. base, 1½ ft. high, W. of the corner.</p>
	<p>From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp.</p> <p>N. 0° 17' 00" W., bet. secs. 34 and 35.</p> <p>Barbed wire fence, bears E. and W.; asc. SW. slope through logged area.</p>

**UNION COUNTY
SURVEYOR**

Date Received 3/5/13

Date Filed 3/5/13

By [Signature]

File No. 076-2013R