UNION COUNTY SURVEYOR

CERTIFIED RECORD OF LAND CORNER MONUMENTATION

HISTORY OF ORIGINAL CORNER ESTABLISHMENT:

Corner originally established by H.M. Thatcher under GLO contract Number 320, dated April 1, 1879. Surveyor General record states:

Set stone 27x17x7 inches for 1/4 cor.

Raised Stone Mound at Cor.

T 5S R 41 E N-11

DESCRIPTION OF CORNER EVIDENCE FOUND:

A 1 1/2"X 24" Iron Pipe marked "CX-19 1973", in a large mound of stone.

DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

At the Pipe location in mound of stone, I set a $2 \frac{1}{2}$ " x 30" Aluminum pipe over the top of existing pipe, with cap marked as shown, 22" in the ground, with mound of stone 4 ft. wide, from which:

NEW BEARING TREES:

At base of 40' wide x 25' high rock outcrop I chiseled an "X BO" on the rock face that, bears North 72° East, a distance of 69.17 feet.

A 21" Ponderosa Pine bears South 78° East, a distance of 44.26 feet, marked 1/4 S21 BT.

A 12" Douglas Fir bears South 52° West, a distance of 43.85 feet, marked 1/4 S21 BT.

A 5" Ponderosa Pine bears North 27° West, a distance of 11.56 feet, marked "X" BT.

Corner falls on a steep South facing hillside, approximately 200 feet North of existing Fish facility.

I hereby certify that the corner was monumented on November 9, 2009.

Witness: Jeff Hsu

REGISTERED PROFESSIONAL LAND SURVEYOR

OREGON

RICK G. ROBINSON

Renewal Date: December 31, 2010

SE COUNTY SURVEY

T 5S R 41E OP

S 16

1/4

S 21

2009

OPLS 2219

SURVEYOR

Date Received 12/2//09

Date Filed 2/9/2010

UNION COUNTY

File Number 005-2010R

I used a steel tape and magnetic compass in the establishment of the new accessories. I used 18° East declination, the distances are to a 60d spike driven into the root crown at the right side of the bearing trees and to the "X" of the X BO chiseled on the rock face. Attached brass washer marked OPLS 2219 to BT blaze of the bearing trees.