

446

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	S-N 1/64 S 22 S 23 1991
	from which A ponderosa pine, 9 ins. diam., bears S. 89° E., 61 lks. dist., mkd. SN 1/64 S23 BT. A ponderosa pine, 27 ins. diam., bears S. 19° W., 139 lks. dist., mkd. SN 1/64 S22 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. From this point, an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, bears N. 60½° W., 0.205 chs. dist.
10.30	Left bank of Catherine Creek, course SW.
11.30	Right bank of Catherine Creek.
12.15	Graveled road, 25 lks. wide, bears N. 70° E. and S. 55° W.; asc. SE. slope.
20.280	Point for the N 1/16 sec. cor. of secs. 22 and 23. Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.
	N 1/16 S 22 S 23 1991
	from which A Douglas fir, 20 ins. diam., bears N. 41° E., 45 lks. dist., mkd. N 1/16 S23 BT. A ponderosa pine, 16 ins. diam., bears N. 35° W., 40 lks. dist., mkd. N 1/16 S22 BT. Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post. The corner is located on a steep SE. slope, 75 lks. W. of a ravine, drains S. 30° E.
	Continue to ascend SE. slope, through moderate timber and light undergrowth.
30.00	Leave timber.
40.560	The cor. of secs. 14, 15, 22, and 23, monumented with the original slate stone, 14 x 12 x 3 ins. (record, 16 x 14 x 4 ins.), firmly set, projecting 6 ins. above ground, with 3 small notches on the S. edge and 2 grooves on the E. face.

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>[Signature]</i>
File No.	080-2013R

447

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 15 S 14 S 22 S 23 1991</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 18 ins. diam., bears N. 11° E., 29 lks. dist., mkd. T5S R41E S14 BT.</p> <p>A ponderosa pine, 18 ins. diam., bears S. 60° E., 92 lks. dist., mkd. T5S R41E S23 BT.</p> <p>A Douglas fir, 26 ins. diam., bears S. 9° W., 68 lks. dist., mkd. T5S R41E S22 BT.</p> <p>A Douglas fir, 11 ins. diam., bears N. 87° W., 48 lks. dist., mkd. T5S R41E S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.</p>
<p>35.75</p> <p>39.715</p>	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 26' 00" W., bet. secs. 14 and 23.</p> <p>Along S. slope changing to SE. slope.</p> <p>Spur, slopes S.</p> <p>The ¼ sec. cor. of secs. 14 and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 3 ins. above ground, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p>
<p>0.30</p> <p>4.50</p>	<p style="text-align: center;">T 5 S R 41 E S 14 ¼ S 23 1971</p> <p>from which bearing trees mkd. by Albright</p> <p>A ponderosa pine, 15 ins. diam., bears N. 9° E., 42 lks. dist., with healed blaze. (Record, N. 10½° E., 43 lks.)</p> <p>A ponderosa pine, 18 ins. diam., bears S. 9° E., 34 lks. dist., with healed blaze. (Record, S. 5½° E., 33½ lks.)</p> <p>S. 89° 08' 30" W., beginning new measurement.</p> <p>Ravine, drains S. 30° E.; asc. E. slope.</p> <p>Spur, slopes SE.; continue along broken S. slope.</p>

UNION COUNTY SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By *D. L. Gilman*

File No. C80-201312