

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
19.730	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} \text{S } 14 \\ \text{W } 1/16 \text{ ---} \\ \text{S } 23 \\ 1991 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears S. 67° W., 71 lks. dist., mkd. W 1/16 S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 63½° W., 85 lks. dist., mkd. W 1/16 S14 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>

39.460	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> <p>N. 0° 45' 00" W., bet. secs. 14 and 15.</p> <p>Ascend along E. edge of rocky ridge.</p>
7.50	<p>Slope changes to W. slope.</p>
40.960	<p>Point for the ¼ sec. cor. of secs. 14 and 15 at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{r} \text{T } 5 \text{ S } \text{ R } 41 \text{ E} \\ \text{S } 15 \text{ } \frac{1}{4} \text{ S } 14 \\ 1991 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 24 ins. diam., bears S. 25° E., 7 lks. dist., mkd. ¼ S14 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 79° W., 179 lks. dist., mkd. ¼ S15 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Continue along W. slope through logged area.</p>
56.60	<p>Graveled road, 25 lks. wide, bears N. 10° W. and S. 30° E.</p>
61.440	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>

<b>UNION COUNTY SURVEYOR</b>	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>MLG</i>
File No.	081-2013R