436

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

	CHAINS		
	COUNTY	A ponderosa pine, 18 ins. diam., bears N. 72½° E., 88 lks. dist., mkd. ¼ S24 BT.	
Date Received	3/5/13	A ponderosa pine, 20 ins. diam., bears S. 16° W., 91 lks. dist., mkd. ½ S23 BT.	
Date Filed	3/5/13	Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.	
By MG	Mur	N. 1° 45′ 00" E., beginning new measurement.	
File No.	83-2013R	Descend steep, broken NE. slope to South Fork of Catherine Creek; thence over spur.	
	35.65	North Fork of Catherine Creek, 100 lks. wide, course S. 70° W.; continue over creek bottom land.	
	37.55	Graveled road, 25 lks. wide, bears N. 80° E. and S. 70° W.; asc. S. slope.	
	39.540	The cor. of secs. 13, 14, 23, and 24, monumented with the original basalt stone, $14 \times 12 \times 6$ ins., loosely set 3 ins. in the ground, with no clear marks. (Loose alongside find an ancient broken wood signboard predating 1953 by its designation of this place as the boundary of the Whitman National Forest.)	
		At the corner point	
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
		T 5 S R 41 E S 14 S 13 S 23 S 24 1991	
		from which new bearing trees	
		A Douglas fir, 16 ins. diam., bears N. 86¼° E., 62 lks. dist., mkd. T5S R41E S13 BT.	
		A Douglas fir, 22 ins. diam., bears S. 3° E., 89 lks. dist., mkd. T5S R41E S24 BT.	
		A ponderosa pine, 16 ins. diam., bears S. 45° W., 68 lks. dist., mkd. T5S R41E S23 BT.	-
		A Douglas fir, 30 ins. diam., bears N. 89° W., 179 lks. dist., mkd. T5S R41E S14 BT.	
		Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.	
		Raise a mound of stone, 4 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.	
	9		