

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>From this point, a ponderosa pine, 33 ins. diam., bears N. 63° 47' E., 2.850 chs. dist., with circular and straight scribe marks visible on opened blazes on the E. and W. sides. This tree mkd. by person(s) unknown.</p>
	<p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp. S. 89° 41' 30" W., bet. secs. 13 and 24.</p>
1.50	<p>Along N. slope, through moderate timber and light undergrowth. Ravine, drains N.; asc. NE. slope.</p>
7.70	<p>Abandoned road, 20 lks. wide, bears N. 20° W. and S. 20° E.</p>
15.00	<p>North edge of rounded butte; desc. NW. slope changing to broken W. slope.</p>
38.300	<p>Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.</p>
<p>UNION COUNTY SURVEYOR</p>	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
Date Received	<p>T 5 S R 41 E S 13 ¼</p>
Date Filed	<p>S 24 1991</p>
By	<p>from which</p>
File No.	<p>A larch, 13 ins. diam., bears S. 42° W., 61 lks. dist., mkd. ¼ S24 BT.</p>
	<p>A ponderosa pine, 17 ins. diam., bears N. 7° W., 57 lks. dist., mkd. ¼ S13 BT.</p>
	<p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p>
55.60	<p>Spur, slopes N. 60° W.; desc. steep W. slope.</p>
57.450	<p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p>
	<p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>
	<p>W 1/16 S 13 S 24 1991</p>
	<p>from which</p>
	<p>A ponderosa pine, 13 ins. diam., bears N. 75½° E., 61 lks. dist., mkd. W 1/16 S13 BT.</p>

438

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
	<p>A ponderosa pine, 17 ins. diam., bears S. 51° W., 82 lks. dist., mkd. W 1/16 S24 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post</p>
67.30	North Fork of Catherine Creek, 50 lks. wide, course S. 40° W.; continue over creek bottom land.
70.00	Graveled road, 25 lks. wide, bears N. 80° E. and S. 80° W.; asc. SE. slope.
76.600	The cor. of secs. 13, 14, 23, and 24.
	N. 0° 43' 30" W., bet. secs. 13 and 14.
9.00	Ascend steep S. slope, through medium timber and light undergrowth.
39.660	Across nearly level bench, changing to SE. slope.
9.00	The ¼ sec. cor. of secs. 13 and 14, monumented with the original unmarked basalt stone, 14 x 12 x 8 ins. (record, 12 x 10 x 8 ins.), firmly set, projecting 6 ins. above ground, with remains of old stone mound alongside.
	At the corner point
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T 5 S R 41 E S 14 S 13 1991</p>
	from which new bearing trees
	A pine, 9 ins. diam., bears N. 78½° E., 24 lks. dist., mkd. ¼ S13 BT.
	A pine, 15 ins. diam., bears N. 89° W., 11 lks. dist., mkd. ¼ S14 BT.
	Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.
	Raise a mound of stone, 4 ft. base, 1½ ft. high, W. of the corner.
	From the standard cor. of secs. 34 and 35 on the S. bdy. of the Tp.
	N. 0° 17' 00" W., bet. secs. 34 and 35.
0.10	Barbed wire fence, bears E. and W.; asc. SW. slope through logged area.

UNION COUNTY
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

M. G. Allen

File No.

084-2013R