

Dependent Resurvey of a Portion of the East Boundary,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS																
	<p>N. 2° 21' 00" W., beginning new measurement.</p> <p>Ascend over steep SW. slope.</p>															
9.25	<p>Dirt road, 25 lks. wide, bears N. 20° W. and S. 20° E.</p>															
29.00	<p>Spur, slopes N. 60° W.</p>															
30.75	<p>Graveled road, 25 lks. wide, bears E. and W.; desc. steep N. slope.</p>															
35.50	<p>Abandoned dirt road, 25 lks. wide, bears E. and W.</p>															
37.875	<p>From this point, the original closing cor. of secs. 18 and 19, T. 5 S., R. 42 E., bears East, 0.025 chs. dist., monumented with the original basalt stone, 13 x 7 x 6 ins. (record, 12 x 6 x 5 ins.), loosely set 3 ins. in the ground, mkd. CC on the E. face and a cross on top, from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A fir snag, 15 ins. diam., bears N. 83° E., 17 lks. dist., with scribe marks S R42E S18 CC legible on opened blaze. (Record, N. 75° E.)</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>															
<p style="text-align: center;">UNION COUNTY SURVEYOR</p> <p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/13</u></p> <p>By <u>RLG/MLM</u></p> <p>File No. <u>086-2013R</u></p>	<table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">T 5 S</td> <td style="border-left: 1px solid black; padding-left: 10px;">T 5 S</td> <td></td> </tr> <tr> <td style="padding-right: 10px;">R 41 E</td> <td style="border-left: 1px solid black; padding-left: 10px;">S 18</td> <td></td> </tr> <tr> <td></td> <td style="border-left: 1px solid black; padding-left: 10px;">S 19</td> <td style="padding-left: 10px;">CC</td> </tr> <tr> <td style="padding-right: 10px;">S 24</td> <td style="border-left: 1px solid black; padding-left: 10px;">R 42 E</td> <td></td> </tr> <tr> <td></td> <td></td> <td style="text-align: center;">1991</td> </tr> </table> <p>from which new bearing trees</p> <p>A fir, 19 ins. diam., bears N. 83½° E., 31 lks. dist., mkd. T5S R42E S18 CC BT.</p> <p>A lodgepole pine, 9 ins. diam., bears S. 28½° E., 52½ lks. dist., mkd. T5S R42E S19 CC BT.</p>	T 5 S	T 5 S		R 41 E	S 18			S 19	CC	S 24	R 42 E				1991
T 5 S	T 5 S															
R 41 E	S 18															
	S 19	CC														
S 24	R 42 E															
		1991														
39.315	<p>Deposit a white "DEEP-1" magnetic marker at the base, the corner stone alongside, and set a 6 ft. steel fence post alongside the stainless steel post.</p>															
39.315	<p>The cor. of secs. 13 and 24 only, monumented with the original basalt stone, 14 x 12 x 8 ins. (record, 16 x 14 x 8 ins.), firmly set in the remains of an old stone mound, with 3 notches on the N. edge.</p> <p>At the corner point</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>															

423

**Dependent Resurvey of a Portion of the East Boundary,
T. 5 S., R. 41 E., Willamette Meridian, Oregon**

CHAINS

T 5 S T 5 S
S 13 | R 42 E
S 24 | S 18
R 41 E
1991

from which new bearing trees

A fir, 20 ins. diam., bears S. 34° W., 52½ lks. dist.,
mkd. T5S R41E S24 BT.

A larch, 7 ins. diam., bears N. 16½° W., 104 lks. dist.,
mkd. X at breast height and BT at the base.

Deposit a white "DEEP-1" magnetic marker at the base and the
corner stone alongside the stainless steel post.

**Dependent Resurvey of a Portion of the West Boundary,
T. 5 S., R. 41 E., Willamette Meridian, Oregon**

(Restoring the survey by Henry M. Thatcher in 1879)

From the standard cor. of Tps. 5 S., Rs. 40 and 41 E.

N. 0° 18' 00" E., bet. secs. 31 and 36.

Ascend S. slope through low brush and scattering timber.

20.00

Slope changes to W. slope.

40.860

The ¼ sec. cor. of secs. 31 and 36, perpetuated and recorded by
Duane I. Griffith, Registered Land Surveyor No. 644, in 1986,
recorded under file No. 55-86R, monumented with an aluminum post,
2½ ins. diam., firmly set with top flush with the ground surface,
and in a collar of stone, with aluminum cap mkd.

BAGETT GRIFFITH ASSOC
T 5 S
R 40 E ¼ R 41 E
S 36 | S 31
1986
OPLS 644

from which the remains of the original bearing trees

A root hole with rotten remains of a pine stump within,
bears S. 11° E., 13 lks. dist., with scribe marks ¼S
on one detached blaze alongside and scribe marks BT
on second detached blaze alongside.

A sawed pine stump, 30 ins. diam., bears N. 50° W.,
75 lks. dist., no marks. (Record, 73 lks.)

and bearing trees mkd. by Griffith

**UNION COUNTY
SURVEYOR**

Date Received

3/5/13

Date Filed

3/5/13

File No.

086-2013R