


**CERTIFIED RECORD OF LAND CORNER MONUMENTATION**

**HISTORY OF ORIGINAL CORNER ESTABLISHMENT:**  
 Corner not previously established.

T 5S R 41 E O-13



**DESCRIPTION OF CORNER EVIDENCE FOUND:**  
 None

See Minor Partition Number 20100001T  
**DESCRIPTION OF MONUMENT AND ACCESSORIES I ESTABLISHED**

**TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**  
 At position determined by survey, I set a 5/8" x 30" iron rod with 2 1/2" Aluminum Cap marked as shown, 26 ins. in the ground, from which:


**BEARING TREES:**  
 A 25 in. Ponderosa Pine bears South 39° East, a distance of 64.72 feet,  
 marked N 1/16 S22 BT.  
 a 20 in. Ponderosa Pine bears North 3° West, a distance of 51.55 feet,  
 marked N 1/16 S21 BT.

I hereby certify that the corner was set on November 30, 2009.

Set a steel fencepost 1 ft. North of corner monument. An East/West fence runs approx. 60 ft. South of corner.

Witness: Jeff Hsu, Gregory T. Blackman, Jr.

**REGISTERED  
 PROFESSIONAL  
 LAND SURVEYOR**



**OREGON**  
July 17, 1986

**RICK G. ROBINSON**  
 2219

Renewal Date: December 31, 2010

BAGETT - GRIFFITH & BLACKMAN

T 5S R 41 E

N 1/16

S 21 | S 22

2009

OPLS 2219

**UNION COUNTY  
 SURVEYOR**

---

Date Received 1/6/2010

Date Filed 2/9/2010

Filed By \_\_\_\_\_

File Number 001-2010R

I used a steel tape and magnetic compass in the establishment of the accessories. I used 18° East declination, the distances are to a 60d spike driven into the root crown at the right side of the bearing trees. Attached brass washer marked OPLS 2219 to BT blaze.