

446

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
<p>UNION COUNTY SURVEYOR</p> <p>Date Received <u>3/5/13</u></p> <p>Date Filed <u>3/5/13</u></p> <p>By <u>R.L. Gallen</u></p> <p>File No. <u>087-7013R</u></p>	<p style="text-align: center;">S-N 1/64 S 22 S 23 1991</p> <p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears S. 89° E., 61 lks. dist., mkd. SN 1/64 S23 BT.</p> <p>A ponderosa pine, 27 ins. diam., bears S. 19° W., 139 lks. dist., mkd. SN 1/64 S22 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>From this point, an iron rod, 5/8 in. diam., firmly set, projecting 10 ins. above ground, bears N. 60½° W., 0.205 chs. dist.</p>
<p>10.30</p> <p>11.30</p> <p>12.15</p>	<p>Left bank of Catherine Creek, course SW.</p> <p>Right bank of Catherine Creek.</p> <p>Graveled road, 25 lks. wide, bears N. 70° E. and S. 55° W.; asc. SE. slope.</p>
<p>20.280</p>	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">N 1/16 S 22 S 23 1991</p> <p>from which</p> <p>A Douglas fir, 20 ins. diam., bears N. 41° E., 45 lks. dist., mkd. N 1/16 S23 BT.</p> <p>A ponderosa pine, 16 ins. diam., bears N. 35° W., 40 lks. dist., mkd. N 1/16 S22 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>The corner is located on a steep SE. slope, 75 lks. W. of a ravine, drains S. 30° E.</p> <p>Continue to ascend SE. slope, through moderate timber and light undergrowth.</p>
<p>30.00</p>	<p>Leave timber.</p>
<p>40.560</p>	<p>The cor. of secs. 14, 15, 22, and 23, monumented with the original slate stone, 14 x 12 x 3 ins. (record, 16 x 14 x 4 ins.), firmly set, projecting 6 ins. above ground, with 3 small notches on the S. edge and 2 grooves on the E. face.</p>