


P-17 T55 R41E

CORNER RECORD (PERPETUATION)

MONUMENT: DESCRIBE NEW MONUMENT SET, OR WORK DONE TO PRESERVE EXISTING MONUMENT

2 1/2" IRON Post 28" Long set 22" IN GROUND
with 5' steel Fence Post Along side
Deposit ORIGINAL Stone Along side IRON Post



ACCESSORIES DESCRIBE NEW BT'S WITNESS OBJECTS ETC. ESTABLISHED, OR WORK DONE TO PRESERVE EXISTING EVIDENCE

A FIR 12" BRS N 62° E 44 LKS MKD 1/4 S23 BT
A FIR 13" BRS S 20° W 63 LKS MKD 1/4 S22 BT

Work Done By S ALBRIGHT Title CADASTRAL SURVEYOR Date 7/24/71 State Registration No. or Agency RI 8 838 BLM

Certified Cor. Record Prepared? Yes No Filed At: _____ Date _____

REMARKS

Index File No.	T.	R.	M.	Tract or Surv. No.	Cor.

UNION COUNTY SURVEYOR

Date Received _____

Date Filed 12-28-87

By G. LANGLITZ, DEPUTY

File No. 430-87R

P-17

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
19.245	<p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 22 S 23 1991</p> <p>from which</p> <p style="padding-left: 40px;">A larch, 35 ins. diam., bears S. 45° E., 26 lks. dist., mkd. S 1/16 S23 BT.</p> <p style="padding-left: 40px;">A larch, 8 ins. diam., bears N. 30° W., 26 lks. dist., mkd. S 1/16 S22 BT.</p> <p>Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.</p> <p>Ascend SW. slope</p>
38.490	<p>The ¼ sec. cor. of secs. 22 and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 41 E S 22 ¼ S 23 1971</p> <p>from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A fir, 37 ins. diam., bears S. 68° E., 29 lks. dist., with fragmentary scribe marks and axe marks in opened blaze. (Record, S. 71° E.)</p> <p style="padding-left: 40px;">A root hole, bears S. 70° W., 31 lks. dist., with rotten pine log alongside, 30 ins. diam., with axe marks.</p> <p>and bearing trees mkd. by Albright</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 60½° E., 44 lks. dist., with healed blaze. (Record, N. 62° E.)</p> <p style="padding-left: 40px;">A fir, 16 ins. diam., bears S. 18½° W., 63 lks. dist., with healed blaze. (Record, S. 20° W.)</p>
	<p>N. 1° 21' 00" E., beginning new measurement.</p> <p>Descend NW. slope.</p> <p>Point for the S-N 1/64 sec. cor. of secs. 22 and 23.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a collar of stone, with brass cap mkd.</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>[Signature]</i>
File No.	092-2013R

Remonumentation of Certain Original Corner Points,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

The 1/4 sec. cor. of secs. 22 and 23, monumented with the original basalt stone, 17 x 9 x 7 ins., loosely set 5 ins. in the ground, with illegible chisel marks visible on N. face, from which the original bearing trees:

A fir, 33 ins. diam., bears S. 71° E., 29 lks. dist., with scribe mark S visible on opened blaze.

A root hole, bears S. 70° W., 31 lks. dist., with a down ponderosa pine alongside, 36 ins. diam., no marks visible.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 5 S R 41 E
1/4
S 22 | S 23
1971

from which new bearing trees

A fir, 12 ins. diam., bears N. 62° E., 44 lks. dist., mkd. 1/4 S23 BT.

A fir, 13 ins. diam., bears S. 20° W., 63 lks. dist., mkd. 1/4 S22 BT.

Deposit corner stone and set 5 ft. steel fence post alongside iron post.

The 1/4 sec. cor. of secs. 14 and 23, monumented with the original basalt stone, 21 x 7 x 7 ins., firmly set 6 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with illegible chisel marks visible on N. face.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 5 S R 41 E
1/4
S 14
S 23
1971

from which new bearing trees

A ponderosa pine, 11 ins. diam., bears N. 10 1/2° E., 43 lks. dist., mkd. 1/4 S14 BT.

A ponderosa pine, 16 ins. diam., bears S. 5 1/2° E., 33 1/2 lks. dist., mkd. 1/4 S23 BT.

Deposit corner stone and set 5 ft. steel fence post alongside iron post.

The corner is located in old fence line, bears E. and W.

The 1/4 sec. cor. of secs. 21 and 28, monumented with the original basalt stone, 25 x 15 x 9 ins., firmly set 14 ins. in the ground, with illegible chisel marks visible on N. face, and in a mound of stone, 2 ft. base, to top.

UNION COUNTY SURVEYOR

Date Received 3/5/13

Date Filed 3/5/13

By W. G. Gilman

File No. 012-2013R