

Dependent Resurvey of a Portion of the East Boundary,  
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS													
	Ascend over SW. slope, through medium timber and light undergrowth.												
19.960	Point for the S 1/16 sec. cor. of sec. 24 only.												
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.												
	<div style="text-align: center;"> <table border="0"> <tr><td>S 1/16</td><td> </td><td></td></tr> <tr><td>S 24</td><td> </td><td></td></tr> <tr><td>1991</td><td> </td><td></td></tr> </table> </div>	S 1/16			S 24			1991					
S 1/16													
S 24													
1991													
	from which												
	A ponderosa pine, 25 ins. diam., bears N. 82° W., 33 lks. dist., mkd. S 1/16 S24 BT.												
	A ponderosa pine, 12 ins. diam., bears N. 37° W., 27 lks. dist., mkd. X at breast height and BT at the base.												
	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.												
22.20	Spur, slopes W.												
33.60	Gravel road, 20 lks. wide, bears irregularly E. and W.; asc. S. slope.												
35.675	From this point, a stone, 17 x 13 x 5 ins., firmly set, sides facing E. and W., projecting 8 ins. above the ground, with no marks, bears West, 0.183 chs. dist. I bury this stone in place.												
36.00	Spur, slopes SW.												
39.920	The ¼ sec. cor. of sec. 24 only, monumented with the original slate stone, 18 x 14 x 5 ins. (record, 17 x 14 x 5 ins.), loosely set at the center of an ancient stone mound, no marks.												
	At the corner point												
	Set a stainless steel post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.												
	<div style="text-align: center;"> <table border="0"> <tr><td>T 5 S</td><td> </td><td></td></tr> <tr><td>R 41 E</td><td> </td><td>R 42 E</td></tr> <tr><td>¼ S 24</td><td> </td><td></td></tr> <tr><td>1991</td><td> </td><td></td></tr> </table> </div>	T 5 S			R 41 E		R 42 E	¼ S 24			1991		
T 5 S													
R 41 E		R 42 E											
¼ S 24													
1991													
	from which new bearing trees												
	A ponderosa pine, 20 ins. diam., bears S. 50° W., 73 lks. dist., mkd. ¼ S24 BT.												
	A ponderosa pine, 10 ins. diam., bears N. 81° W., 39 lks. dist., mkd. X at breast height and BT at the base.												
	Deposit a white "DEEP-1" magnetic marker at the base and the corner stone alongside the stainless steel post.												

UNION COUNTY  
SURVEYOR

Date Received

3/5/13

Date Filed

3/5/13

By

*[Signature]*

File No.

094-2013R