

426

Dependent Resurvey of a Portion of the West Boundary,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS	
40.200	<p>The cor. of secs. 19, 24, 25, and 30 reestablished by proportionate measurement by Duane I. Griffith, Registered Surveyor No. 644, in 1986, recorded under file No. 58-86R; there is no remaining evidence of the original corner, therefore, this position is accepted as the corner, monumented with an aluminum post, 2½ ins. diam., firmly set flush with the ground, and in a collar of stone, with aluminum cap mkd.</p> <p style="text-align: center;">BAGETT GRIFFITH ASSOC T 5 S R 40 E R 41 E S 24 S 19 S 25 S 30 1986 OPLS 644</p> <p>from which bearing trees mkd. by Griffith</p> <p>A fir, 14 ins. diam., bears N. 19° E., 50 lks. dist., with fragmentary scribe marks on partially healed double blaze.</p> <p>A fir, 9 ins. diam., bears S. 28° E., 40 lks. dist., with healed double blaze.</p> <p>A fir, 20 ins. diam., bears S. 29° W., 71 lks. dist., with pitch covered blaze.</p> <p>A larch, 12 ins. diam., bears N. 3° W., 52 lks. dist., with fragmentary scribe marks on partially healed double blaze.</p> <p>and a new bearing tree</p> <p>A ponderosa pine, 10 ins. diam., bears S. 60° E., 69 lks. dist., mkd. T5S R41E S30 BT.</p> <p>A steel fence post is set alongside the aluminum post.</p>
0.15	Barbed wire fence, extends E. and W.
14.00	Ascend SE. slope
20.100	<p>Point for the S 1/16 sec. cor. of secs. 19 and 24.</p> <p>Set a stainless steel post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S 24 S 19 1992</p>

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>MLG</i>
File No.	095-2013R

427

Dependent Resurvey of a Portion of the West Boundary,
T. 5 S., R. 41 E., Willamette Meridian, Oregon

CHAINS

from which

A ponderosa pine, 12 ins. diam., bears S. 28° E.,
52 lks. dist., mkd. S 1/16 S19 BT.

A ponderosa pine, 12 ins. diam., bears N. 7½° W.,
40 lks. dist., mkd. S 1/16 S24 BT.

Deposit a white "DEEP-1" magnetic marker at the base and set a
steel fence post alongside the stainless steel post.

The corner is located 15 lks. E. of a barbed wire fence, extending
N. and S.

27.00 Top of ascent; along E. slope.

40.200 The ¼ sec. cor. of secs. 19 and 24, perpetuated from the original
corner stone, no longer visible, and recorded by Duane I.
Griffith, Registered Land Surveyor No. 644, in 1986, recorded
under file No. 64-86R, monumented with an aluminum post, 2½ ins.
diam., firmly set with top flush with the ground, and in a collar
of stone, 2½ ft. base, to top, with aluminum cap mkd.

BAGETT GRIFFITH ASSOC
T 5 S
R 40 E ¼ R 41 E
S 24 | S 19
1986
OPLS 644

from which bearing trees mkd. by Griffith

A ponderosa pine, 18 ins. diam., bears S. 10° E.,
99 lks dist., with fragmentary scribe marks on
partially healed double blaze.

A ponderosa pine, 18 ins. diam., bears N. 49° W.,
131½ lks. dist., with fragmentary scribe marks
on partially healed double blaze.

A steel fence post is set alongside the aluminum post.

The corner is located at the top of a steep NE. slope 60 lks. E.
of a barbed wire fence, extending N. and S.

From the ¼ sec. cor. of secs. 13 and 18 perpetuated and recorded
by Duane I. Griffith, Registered Land Surveyor No. 644, in 1986,
recorded under file No. 76-86R, monumented with an aluminum post,
2½ ins. diam., firmly set in a collar of stone, with top flush
with the ground, with aluminum cap mkd.

BAGETT GRIFFITH ASSOC
T 5 S
R 40 E ¼ R 41 E
S 13 | S 18
1986
OPLS 644

from which bearing trees mkd. by Griffith

UNION COUNTY SURVEYOR	
Date Received	3/5/13
Date Filed	3/5/13
By	<i>M. Galun</i>
File No.	095-2013R