460

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 41 E., Willamette Meridian, Oregon

ĺ	CHAINS		
	8.00	Along W. slope.	
	20.450	Point for the S 1/16 sec. cor. of secs. 21 and 22.	
		Set a stainless steel post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
		s 1/16 s 21 s 22 1991	
		from which	
		A ponderosa pine, 16 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ E., 68 lks. dist., mkd. S 1/16 S22 BT.	
		A ponderosa pine, 13 ins. diam., bears S. $25\frac{1}{4}^{\circ}$ W., 34 lks. dist., mkd. S $1/16$ S21 BT.	
		Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.	
	24.00	Descend NW. slope.	
	37.00	Descend steep N. slope.	
	40.900	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22, at proportionate distance; there is no remaining evidence of the original corner.	
		Set a stainless steel post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a collar of stone, with brass cap mkd.	
UNION C SURV	OUNTY EYOR	T 5 S R 41 E S 21 S 22 1991	
Date Received	3/5/13	from which	-
Date Filed	3/5/13	A larch, 12 ins. diam., bears S. 50½° E., 10 lks. dist., mkd. ½ S22 BT.	
ey MLG.	llur	A larch, 12 ins. diam., bears N. 59½° W., 26 lks. dist., mkd. ¼ S21 BT.	CONTRACTOR
Ey 10 6	96-70 BR	Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.	-
		Descend steep N. slope to Catherine Creek; thence across creek and flat bottom land and asc. SW. slope.	-
	81.800	The cor. of secs. 15, 16, 21, and 22, monumented with the original unmarked slate stone, 25 x 14 x 6 ins. (record, 24 x 18 x 8 ins.), loosely set at the center of an old stone mound. Alongside find a water pipe, 2 ins. diam., firmly set, projecting 3 ins. above ground, with washer mkd. CX 18 1975.	
		At the corner point	
			_